



Faculty of Engineering

**PROPERTIES OF POLYSTYRENE CONCRETE BRICKS WITH
SAWDUST ASH**

Mcfarlane Chua Kang Wei

**Bachelor of Engineering with Honours
(Civil Engineering)
2009**

UNIVERSITI MALAYSIA SARAWAK

R13a

BORANG PENGESAHAN STATUS TESIS

Judul: PROPERTIES OF POLYSTYRENE CONCRETE BRICKS WITH SAWDUST ASH

SESI PENGAJIAN: 2008/2009

Saya MCFARLANE CHUA KANG WEI

(HURUF BESAR)

mengaku membenarkan tesis * ini disimpan di Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dengan syarat-syarat kegunaan seperti berikut:

1. Tesis adalah hakmilik Universiti Malaysia Sarawak.
2. Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dibenarkan membuat salinan untuk tujuan pengajian sahaja.
3. Membuat pendigitan untuk membangunkan Pangkalan Data Kandungan Tempatan.
4. Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dibenarkan membuat salinan tesis ini sebagai bahan pertukaran antara institusi pengajian tinggi.
5. ** Sila tandakan (✓) di kotak yang berkenaan

SULIT (Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia seperti yang termaktub di dalam AKTA RAHSIA RASMI 1972).

TERHAD (Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi/badan di mana penyelidikan dijalankan).

TIDAK TERHAD

Disahkan oleh

(TANDATANGAN PENULIS)

(TANDATANGAN PENYELIA)

Alamat tetap: 262,LRG7,JLN SENGGUON

93250, KUCHING, SARAWAK

CIK IDAWATI ISMAIL

Nama Penyelia

Tarikh: 20 APRIL 2009

Tarikh: 20 APRIL 2009

CATATAN

- * Tesis dimaksudkan sebagai tesis bagi Ijazah Doktor Falsafah, Sarjana dan Sarjana Muda.
- ** Jika tesis ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyatakan sekali sebab dan tempoh tesis ini perlu dikelaskan sebagai SULIT dan TERHAD.

The Following Final Year Project:

Title : Properties of Polystyrene Concrete Bricks with Sawdust Ash

Author : Mcfarlane Chua Kang Wei

Matrix Number : 14455

Was read and certified by:

Cik Idawati Ismail

Project Supervisor

Date

**PROPERTIES OF POLYSTYRENE CONCRETE BRICKS WITH
SAWDUST ASH**

Mcfarlane Chua Kang Wei

A thesis submitted in partial fulfilment of the requirements for the award of
the degree of Bachelor of Engineering with Honours
(Civil Engineering)

Faculty of Engineering
UNIVERSITI MALAYSIA SARAWAK
2009

To my beloved family

AKNOWLEDGEMENT

In this very special page, I wish to extend my heartfelt gratitude to the numerous people who have helped me over the long haul.

I wish to convey my appreciation to my thesis supervisor, Cik Idawati Ismail for her contribution, dedication and patience in conducting my research. I am also grateful to the technicians of Civil Engineering laboratory, En. Nur Adha Abdul Wahab who have helping me in the laboratory works.

Last but not least, I would like to reach out and thanks to my beloved family who were there to support and encourage me through my difficult time. I also would like to thanks to my fellow course mate who have give me advice and helping me in my research.

ABSTRAK

Projek ini dijalankan untuk mengkaji ketahanan dan sifat bata konkrit polistirena yang mengandungi abu sisa-sisa kayu. Biji-bijian polistirena padat sebagai bahan ringan digunakan untuk menggantikan pasir di dalam adunan konkrit manakala abu sisa-sisa kayu sebagai pengantian simen. Sejumlah 216 bata dengan saiz 195 mm x 100 mm x 65 mm (panjang x lebar x tinggi) disediakan. Enam kajian dijalankan untuk mengkaji dan membanding sifat-sifat konkrit polistirena. Kajian-kajian yang dijalankan ialah ujian daya kemampatan, penyerapan air, ujian serangan air laut, berat dan ketumpatan, saiz dan ujian serangan asid. Kekuatan mampatan bata bergantung kepada jenis-jenis bahan yang dicampurkan dan nisbahnya. Walaubagaimanapun, kandungan abu sisa-sisa kayu yang banyak mengurangkan kekuatan konkrit, tetapi keputusan memaparkan abu sisa-sisa kayu boleh menyumbang kekuatan kepada konkrit dalam masa pengawetan yang panjang. Bata yang dikaji dalam air laut dibandingkan dengan bata yang dikaji dalam air paip. Keputusan mendapati berat dan ketumpatan yang rendah akan meninggikan kadar penyerapan air. Abu sisa-sisa kayu juga mempengaruhi kadar penyerapan air kerana ia adalah bahan-bahan yang berupaya untuk menyerap air. Kekuatan bata-bata yang dikaji dalam air laut mempunyai kekuatan mampatan yang lebih rendah berbanding dengan bata-bata yang dikaji dalam air paip. Bata-bata yang dikaji dengan ujian serangan asid didapati perubahan fizikal dari segi rupa luaran, berat dan ketumpatan, dan dimensi. Perubahan fizikal bagi bata konkrit polistirena lebih tinggi dengan kandungan biji-bijian polistirena dan abu sisa-sisa kayu yang tinggi di dalam adunan.

ABSTRACT

This project was carried out to investigate the mechanical and durability properties of hardened polystyrene concrete bricks containing sawdust ash. In this study, polystyrene beads as lightweight aggregate are used to replace fine aggregate in the concrete mixture whereas sawdust ash is for replacement of cement. A total of 216 bricks with the size of 195 mm x 100 mm x 65 mm (length x width x height) were prepared. Six tests were carried out to investigate and compared the properties of polystyrene concrete bricks. The tests were compressive strength test, water absorption, sea water attack, weight and density, dimension and acid attack. The compressive strength of bricks was depended on the materials mixed and the ratio used. Although higher ash content decreased the strength of concrete, the test result indicated that sawdust ash can contribute strength to concrete at longer curing periods. The bricks tested in sea water were compared with the bricks tested in tap water. The result shows the bricks with low weight and density recorded high water absorption rate. Sawdust ash also influenced the water absorption as it is a good water absorbing materials. The bricks tested in sea water recorded lower compressive strength than bricks tested in tap water. The bricks tested in acid attack also show changes in physical properties such as appearance, weight and density and dimension. The changes of properties of polystyrene concrete bricks are much higher for high content of polystyrene beads and sawdust ash in the mix.

TABLE OF CONTENT

	PAGE
DEDICATION	i
ACKNOWLEDGEMENT	ii
ABSTRAK	iii
ABSTRACT	iv
TABLE OF CONTENT	v
LIST OF TABLES	x
LIST OF FIGURES	xi
LIST OF SYMBOL	xiii

CHAPTER 1 INTRODUCTION	1
1.1 General Background	1
1.2 Problem Statement	3
1.3 Objectives	5
1.4 Scope of Works	5
1.5 Outline of the Project	6
1.6 Project Planning	7
CHAPTER 2 LITERATURE REVIEW	8
2.1 Introduction	8
2.2 Admixture in Concrete	9
2.3 Bricks	10
2.4 Expanded Polystyrene Beads	12
2.5 Sawdust	15
2.6 Durability	17
2.7 Polystyrene Concrete	18
2.8 Previous Research	19
2.8.1 Strength of Lightweight Concrete	19
2.8.2 Workability of Lightweight Concrete	22
2.8.3 Water Absorption and Moisture Migration	24
2.8.4 Permeability	26
2.8.5 Drying Shrinkage	27
2.8.6 Weight and Density	28

2.8.7	Chemical Attack	28
2.9	Conclusion	29
CHAPTER 3 METHODOLOGY		30
3.1	Introduction	30
3.2	Raw Materials	31
3.2.1	Cement	33
3.2.2	Expanded Polystyrene Beads	34
3.2.3	Fine Aggregates	34
3.2.4	Superplasticizers	35
3.2.5	Water	36
3.3	Equipments	37
3.3.1	Brick Mould	37
3.3.2	Electronic Weighing Machine	38
3.3.3	Sieve Machine	39
3.3.4	Tamping Rod	39
3.3.5	Cylinder	40
3.3.6	Ratio Box	41
3.3.7	Mixer	42
3.3.8	Slump Cone	42
3.4	Production of EPS Concrete Brick	43
3.5	Experimental	44
3.5.1	Compressive Strength Test	44

3.5.2	Dimension Test	46
3.5.3	Sea Water Resistance	46
3.5.4	Slump Test	46
3.5.5	Density test	47
3.5.6	Absorption Test	48
3.5.7	Acid Resistance	49
3.6	Expected Problems	49
CHAPTER 4 RESULT AND ANALYSIS		50
4.1	Introduction	50
4.2	Workability	50
4.3	Sieve Analysis	52
4.4	Compressive Strength Test	55
4.5	Density correlation with compressive strength	59
4.6	Water absorption and compressive strength	61
4.7	Dimension Test	63
4.8	Weight and Density Test	65
4.9	Water Absorption Test	67
4.10	Acid Resistance	69
4.10.1	Physical appearance of Bricks	70
4.11	Sea Water Resistance	73
4.12	Comparison of Density Under Different Condition	74
4.13	Conclusion	78

CHAPTER 5 CONCLUSION AND RECOMMENDATIONS	79
5.1 Conclusion	79
5.2 Limitation	82
5.3 Recommendation	83
REFERENCES	84
LIST OF APPENDIX	89
Appendix A	89
Appendix B	93
Appendix C	97
Appendix D	101
Appendix E	105
Appendix F	109

LIST OF TABLES

Table No.		Pages
2.1	Characterisation of workability for polystyrene aggregate concrete	24
2.2	Percentage Volume of Water Absorption	25
3.1	Ratio of samples prepared	31
3.2	Volume of mix for different type of ratio	32
3.3	Type of test and number of samples	33
3.4	Fine aggregate grading limit	35
4.1	Slump height for different sample mix	51
4.2	Sieve analysis data	53
4.3	Average compressive strength test result	55
4.4	Brick classification according to MS 76: 1972	58
4.5	Data for relationship between compressive strength and density	59
4.6	Data for relationship between compressive strength and water absorption	61
4.7	Dimension according to MS 76; 1972	64
4.8	Dimension of bricks for reduction tolerance	64

LIST OF FIGURES

Figure No.		Pages
2.1	Expanded polystyrene	13
2.2	Sawdust	15
3.1	EPS waste	34
3.2	Making the brick mould	38
3.3	Brick mould	38
3.4	Electronic weighing machine	38
3.5	Sieve machine	39
3.6	Tamping rod	40
3.7	Cylinder	40
3.8	Ratio box	41
3.9	Mixer	42
3.10	Slump cone	42
3.11	Materials prepared	43
3.12	Compressive test machine	45
4.1	Size distribution of sand and EPS	54
4.2	Comparison of compressive strength of each sample	56

4.3	Relationship between average compressive strength and average density	60
4.4	Relationship between average compressive strength and average percentage of water absorption	62
4.5	Types of measurements of bricks	63
4.6	Brick samples put outside the lab	66
4.7	Relationship between percentage of water absorption and time	67
4.8	Physical changes of the brick samples	71
4.9	Damage of the bricks	73
4.10	Relationship between density and time for sample A	75
4.11	Relationship between density and time for sample B	75
4.12	Relationship between density and time for sample C	76
4.13	Relationship between density and time for sample D	76
4.14	Relationship between density and time for sample E	77
4.15	Relationship between density and time for sample F	77

LIST OF SYMBOLS

%	Percentage
kg/m ³	Kilogram per metre cube
MPa	Mega Pascal
mm	millimeter
°C	Degree of Celsius
m ³	metre cube
kN/s	Kilo Newton per second
kN	Kilo Newton
kg	kilogram
m ₁	Wet brick weight
m ₂	Dry brick weight
N/mm ²	Newton per millimeter square

CHAPTER 1

INTRODUCTION

1.1 General Background

Concrete has been in use for hundreds of years. The word concrete comes from the Latin *concretus*, which means “mixed together” or compounded, or "hardened". Concrete is made up through the mixture of cement, aggregate that is coarse aggregate such as crushed stone or gravel plus a fine aggregate commonly sand, water and chemical admixtures. The mixing of concrete and water will form hard and stone-like materials. This process is due to a chemical process known as hydration.

Concrete, was firstly used by Romans in their aqueducts and roadways construction for over 2,000 years. In the passed, Romans used a primitive mix to produced the concrete and used the mortar consisted of small gravel and coarse sand mixed together with hot lime and water. Horse hair is used to reduce shrinkage and some even mix with animal blood for the purpose to make the mix become more durable.

The use of concrete and its cementitious (volcanic) constituents, such as pozzolanic ash, has been made since the day of the Greeks, the Romans, and possibly earlier ancient civilizations. In 1850, J.L.Lambot constructed for the first time a small cement boat for exhibition in the 1855 World's Fair in Paris and Koenen in 1886 published the first manuscript on the theory and design of concrete structures. Many buildings, bridges and liquid containers of reinforced concrete were already constructed by 1920, and the era of linear and circular prestressing began. (Edward G, 1996)

Brick is defined as small unit of building materials and it maybe solid, hollow or architectural terra cotta to use in construction purposes. The size of brick is standard and easy to be hold in one hand. Brick also retain heat, with-stands corrosion and resists fire. All types of brick serve a structural function or decorative function depends on their formation and composition. Concrete brick is made from the mixture of cement, sand, water and cast in the mould and cured. Bricks are easily recycled-mineral materials and can be reused as bedding material in road construction, for sound insulation walls, tennis court material and etc. There are a few types of bricks such as Sand Cement brick, Clay bricks, Calcium Silicate bricks for the construction application and brick's density varies according to the manufacturer and its uses.

Concrete can be classified into three categories that is normal-weight concrete (2400 kg/m^3), lightweight concrete ($< 1800 \text{ kg/m}^3$) and heavyweight concrete ($> 3200 \text{ kg/m}^3$). The strength of concrete is depending on the hydration reaction whereby the strength of concrete increase when less water is added to the mix of concrete. However

concrete is actually mixed with more water not only for the hydration needs but also to give concrete sufficient workability.

Mostly the lightweight concrete with wide range of concrete densities (300–1800 kg/m³) was studied mainly for compressive strength, split tensile strength, moisture migration and absorption. Besides, the shape, size density and strength of aggregate particles can vary significantly, and can therefore influence the properties of the concrete. Aggregate tends to represent a relatively high volume percentage of concrete, to minimize costs of the material.

1.2 Problem Statement

Nowadays, the problem of waste materials such as sawdust, flyash, silica fume, plastic bottle and others which may cause pollution and health problems to the public. Steps have to be taken to decide on the best ways of making waste useful and renewable. Expanded polystyrene foams (EPS) are widely used as packaging material, construction material, and in household appliances as well as many others. EPS has caused environmental pollutions because it is hard to decompose. Therefore, this research has been done to study the utilization of waste EPS in concrete technology.

The normal weight aggregate, natural stone such as limestone and granite is used to produce normal weight concrete. However, due to the increasing demand of concrete,

natural environment and resources are excessively exploited. Therefore, waste materials can be recycled and used as raw material in cement clinker, admixtures in cement, or as aggregates in concrete to produce lightweight concrete.

Lightweight concrete is typically 25% to 35% lighter but its strength equivalent to normal weight concrete and suitable to be used for structural application. The normal concrete has high self weight and the density is range from 2200 kg/m^3 to 2600 kg/m^3 . The high self weight of concrete is considered as an uneconomical structural material. Therefore, lightweight concrete with lighter density will be used to replace normal concrete as structural materials

Lightweight concrete gives better thermal insulation and has higher cement content than normal weight concrete. Lightweight concrete also bring benefits in term of load bearing elements of smaller cross-section area, reduction in the size of foundations, lower pressure applied to the formwork and also reduced the total mass of materials needed with a consequent increase in productivity. (Neville, 2003)

In the future, it is expected that lightweight concrete will move forward in advancement compare to normal concrete. Synthetic aggregate will be made with the properties of more stronger and lighter so that the structural lightweight concrete become better and better.

1.3 Objectives

The objectives of this study are:

- 1) To produce concrete bricks containing polystyrene concrete mixed with sawdust ash
- 2) To test the mechanical and durability properties of EPS concrete brick containing sawdust ash.

1.4 Scope of works

The purpose of this project is to produce lightweight concrete bricks and test the compressive strength of the brick to compare with the normal concrete. The testing of durability to sea water attack is important to make sure the concrete bricks able to withstand the conditions such as weathering action, chemical attack and abrasions throughout the life of a structure. Other testing such as water absorption and density test also will be carried out.

The mixture of EPS concrete brick is cement, sand, expanded polystyrene bead and sawdust ash. Different ratio of the proportion will produce different type of concrete brick with different properties. The sawdust ash is used as concrete replacement in the mixes and to improve the strength of the concrete brick. The sawdust ash may change the physical and properties of the EPS concrete brick such as dimensions and color. The

testing is according to Malaysian Standard, Specification for Bricks and Blocks of Fired Brickearth Clay or Shale Part 2, Metric Units (MS 76:1972).

1.5 Outline of the project

In chapter 1, introduction about this study and some problems statements was discussed. It also shows the objectives and scope of works that will be carried out. Chapter 2 is the literature review where it shows the past research and result which has been done by other peoples. The journal or research information is important to shows a guideline or references which related to this study. Chapter 3 is methodology which explains type of materials and equipments used for the experiments. It also shows the production and experimental test carry out for the samples. In chapter 4, the result and analysis of the samples in different type of testing will be discussed further. Conclusion and recommendations for this study will be discussed in chapter 5.

1.5 Project Planning

Activity / Duration	JULY 2008	AUG 2008	SEPT 2008	OCT 2008	NOV 2008	DEC 2008	JAN 2009	FEB 2009	MAC 2009	APR 2009	MAY 2009
Literature Review											
Lab Preparation. Data Collection.											
Data Analysis											
Report Writing. Final Report.											