



Faculty of Engineering

**3D MODELLING USING SOLIDWORKS: WALL-MOUNTED
RAINWATER TANK FOR STORMWATER DETENTION IN
COMMERCIAL AREAS**

FOO SWEE WEN

Bachelor of Engineering with Honours

(Civil Engineering)

2017

UNIVERSITI MALAYSIA SARAWAK

Grade: _____

Please tick (✓)

Final Year Project Report

☒

Masters

☐

PhD

☐

DECLARATION OF ORIGINAL WORK

This declaration is made on the.....day of2017.

Student's Declaration:

I FOO SWEE WEN, 41283, FACULTY OF ENGINEERING hereby declare that the work entitled 3D MODELLING USING SOLIDWORKS: WALL-MOUNTED RAINWATER TANK FOR STORMWATER DETENTION IN COMMERCIAL AREAS is my original work. I have not copied from any other students' work or from any other sources except where due reference or acknowledgement is made explicitly in the text, nor has any part been written for me by another person.

Date submitted

FOO SWEE WEN (41283)

Supervisor's Declaration:

I DR DARRIEN MAH YAU SENG hereby certifies that the work entitled 3D MODELLING USING SOLIDWORKS: WALL-MOUNTED RAINWATER TANK FOR STORMWATER DETENTION IN COMMERCIAL AREAS was prepared by the above named student, and was submitted to the "FACULTY" as a partial fulfillment for the conferment of B.ENG. (HONS) (CIVIL), and the aforementioned work, to the best of my knowledge, is the said student's work.

Received for examination by:_____

(DR DARRIEN MAH YAU SENG)

Date:_____

I declare that Project/Thesis is classified as (Please tick (√)):

- ☐ **CONFIDENTIAL** (Contains confidential information under the Official Secret Act 1972)*
- ☐ **RESTRICTED** (Contains restricted information as specified by the organisation where research was done)*
- ☒ **OPEN ACCESS**

Validation of Project/Thesis

I therefore duly affirm with free consent and willingly declare that this said Project/Thesis shall be placed officially in the Centre for Academic Information Services with the abiding interest and rights as follows:

- This Project/Thesis is the sole legal property of Universiti Malaysia Sarawak (UNIMAS).
- The Centre for Academic Information Services has the lawful right to make copies for the purpose of academic and research only and not for other purpose.
- The Centre for Academic Information Services has the lawful right to digitalise the content for the Local Content Database.
- The Centre for Academic Information Services has the lawful right to make copies of the Project/Thesis for academic exchange between Higher Learning Institute.
- No dispute or any claim shall arise from the student itself neither third party on this Project/Thesis once it becomes the sole property of UNIMAS.
- This Project/Thesis or any material, data and information related to it shall not be distributed, published or disclosed to any party by the student except with UNIMAS permission.

Student signature _____
()

Supervisor signature: _____
()

Current Address:

LOT 5259, LORONG 2D, TAMAN UNIGARDEN, 94300, KOTA SAMARAHAN, SARAWAK

Notes: * If the Project/Thesis is **CONFIDENTIAL** or **RESTRICTED**, please attach together as annexure a letter from the organisation with the period and reasons of confidentiality and restriction.

[The instrument is duly prepared by The Centre for Academic Information Services]

**3D MODELLING USING SOLIDWORKS: WALL-MOUNTED
RAINWATER TANK FOR STORMWATER DETENTION IN
COMMERCIAL AREAS**

FOO SWEE WEN

This project is submitted in partial fulfilment
of the requirement for the degree of
Bachelor of Engineering with Honours
(Civil Engineering)

Faculty of Engineering
Universiti Malaysia Sarawak

2017

Dedicated To My Beloved Family and Friends.

ACKNOWLEDGEMENT

First and foremost, I would like to express my highest gratitude to my core supervisor, Dr. Darrien Mah Yau Seng of Universiti Malaysia Sarawak from Civil Engineering Department for provision of expertise and technical support during this one year time. He has shown great leadership and patience throughout this thesis. It would be impossible for me to complete this thesis without those superior knowledge and experience. Besides, I would also like to express my sincere thanks towards my co-supervisor, Mr Bartholomew Emily Ayu from DID, Sarawak for giving me the chance to know the normal practices in the industry related to my project.

Next, I also like to express endless gratitude toward Universiti Sarawak Malaysia (UNIMAS) and Department of Engineering for giving me the chance to have my degree education here. Lastly, I am also grateful to my parents, family members, seniors and friends for their explanations and encouragement which help me in completion of this project. Therefore, I would like to extend my sincere gratitude to all of them.

ABSTRACT

Rapid urban growth with increment of paved areas has resulted in increased stormwater runoff within built environments which could lead to flood events. Therefore, rainwater harvesting is one of the common approaches to store the stormwater temporarily to reduce the volume of runoff in dense urban areas. Normally, conventional rainwater harvesting tank has big capacity and it occupies large land spaces. In this project, a wall-mounted rainwater harvesting system is introduced for commercial buildings with limited empty spaces. Due to the large roof catchment area, three storage tanks are proposed to be installed on the building wall to achieve the desired storage capacity. With the aid of Solidworks Flow Simulation, the effectiveness of the wall-mounted rainwater harvesting system is investigated under various inlet designs (T-Inlet, L-Inlet, and Inclined-Inlet) subjected to three pipe sizes (60mm, 90mm and 120mm). It is found that Inclined-Inlet with 120mm pipe is the ideal design for such a system. It has the most balanced characteristics of smooth water flowing, and associated pressures for closed system. Velocities at tank outlets are with the least differences with 0.116m/s in Tank 1, 0.181m/s in Tank 2 and 0.308m/s in Tank 3. Meanwhile, the pressure within the three tanks also gives a close value about 102 kPa. Hence, a wall-mounted rainwater harvesting system is proven of its appropriate fluid dynamics and pressures to be integrated into commercial buildings for urban stormwater management.

ABSTRAK

Pertumbuhan bandar yang pesat dengan pertambahan kawasan berturap telah menyebabkan peningkatan air larian yang boleh membawa kepada kejadian banjir. Oleh itu, penuaian air hujan adalah salah satu pendekatan biasa untuk menyimpan air ribut sementara untuk mengurangkan jumlah air larian di kawasan bandar yang padat. Biasanya, tangki penuaian air hujan konvensional mempunyai kapasiti yang besar dan ia menduduki ruang tanah yang besar. Dalam projek ini, sistem penuaian air hujan yang dipasang di dinding diperkenalkan untuk bangunan komersial dengan ruang kosong yang terhad. Disebabkan oleh kawasan tadahan bumbung besar, tiga tangki simpanan dicadangkan untuk dipasang pada dinding bangunan untuk mencapai kapasiti simpanan yang dikehendaki. Dengan bantuan Solidworks Flow Simulation, keberkesanan sistem penuaian air hujan yang dipasang di dinding disiasat mengikut pelbagai reka bentuk salur masuk (T-Inlet, L-Inlet, dan cenderung-Inlet) tertakluk kepada tiga saiz paip (60mm, 90mm dan 120mm). Didapati bahawa cenderung-Inlet dengan 120mm paip adalah reka bentuk yang sesuai untuk sistem tersebut. Ia mempunyai ciri-ciri yang paling seimbang air lancar mengalir, dan tekanan yang sesuai untuk sistem tertutup. Halaju di outlet tangki memberikan nilai berhampiran iaitu 0.116 m/s dalam Tangki 1, 0.181 m/s dalam Tangki 2 dan 0.308 m/s dalam Tangki 3. Sementara itu, tekanan di dalam tiga tangki juga memberikan nilai berhampiran kira-kira 102 kPa. Oleh itu, sistem penuaian air hujan yang dipasang di dinding terbukti dinamik bendalir yang sesuai dan tekanan untuk diintegrasikan ke dalam bangunan komersial untuk pengurusan air ribut bandar.

TABLE OF CONTENTS

	Page
Acknowledgement	i
Abstract	ii
Abstrak	iii
Table of Contents	iv
List of Tables	vii
List of Figures	viii
List of Abbreviations	xii

CHAPTER 1 INTRODUCTION

1.1	Background	1
1.2	Problem Statement	1
1.3	Objectives	3

CHAPTER 2 LITERATURE REVIEW

2.1	Urban Stormwater Management	4
2.2	Water Sensitive Urban Design (WSUD)	7
2.3	Rainwater Harvesting	9
2.4	3D modelling – SolidWorks Software	14
2.5	Case Study in Universiti Tenaga Nasional	15
2.6	Case study of Central City, Kota Samarahan	19
2.7	Research Gap	20

CHAPTER 3 METHODOLOGY

3.1	Introduction to SolidWorksCAD software	22
3.2	Introduction to SolidWorks Flow Simulation	24
3.3	Flow Chart of the Wall-mounted Rainwater Harvesting Modelling	26
3.4	SolidWorks Model Development	27
3.4.1	Formation of Storage Tank Model	27
3.4.2	Formation of Pipeline Model	36
3.4.3	Formation of Joint Model	38
3.4.4	Assemble of Parts	42
3.4.5	Setting up of SolidWorks Flow Simulation	44

CHAPTER 4 RESULTS AND DISCUSSION

4.1	Introduction	48
4.2	Prototypes of Wall-Mounted Rainwater Harvesting System	49
4.3	Re-Examining the SWMM Model (Wong, 2015)	53
4.4	Simulation Results by SolidWorks Flow Simulation	54
4.4.1	Scenario 1- Simulation with 60mm Pipe	54
4.4.2	Scenario 2 - Simulation with 90mm Pipe	57
4.4.3	Scenario 3 - Simulation with 120mm pipe	61

CHAPTER 5 CONCLUSIONS AND RECOMMENDATIONS

5.1	Conclusions	66
5.2	Recommendations	67

LIST OF TABLES

Table		Page
2.1	Components in Rainwater Harvesting System	11
2.2	a) Velocity Distribution, b) Pressure Distribution, and c) Turbulent Kinetic Energy Distribution for 20L/s, 30L/s and 40L/s	18
2.3	Numbers of Rainwater Harvesting Tank for each Scenario	20
4.1	Design Parameters from Wong (2015)’s Project	48
4.2	Results Generated from the SWMM Model	53
4.3	Comparison of Scenario 1 between the SolidWorks and SWMM	56
4.4	Simulated Velocities at Inlet and Outlet of Tanks for Scenario 1	56
4.5	Simulated Pressures at Inlet and Outlet of Tanks for Scenario 1	57
4.6	Comparison of Scenario 2 between SolidWorks and SWMM	59
4.7	Simulated Velocities at Inlet and Outlet of Tanks for Scenario 2	59
4.8	Simulated Pressures at Inlet and Outlet of Tanks for Scenario 2	59
4.9	Comparison of Scenario 3 between SolidWorks and SWMM	62
4.10	Simulated Velocities at Inlet and Outlet of Tanks for Scenario 3	63
4.11	Simulated Pressures at Inlet and Outlet of Tanks for Scenario 3	63
4.12	Summary of CFD Analysis	64

LIST OF FIGURES

Figure		Page
1.1	Selected Commercial Lot is Located at Central City, Kota Samarahan	2
1.2	Design Layout of the Wall-Mounted Rainwater Harvesting Tank for Commercial Lot	2
2.1	Zero Uncontaminated Discharge Principle	5
2.2	Typical Stormwater Management Measures	6
2.3	Nature, Urban and WSUD Water Balance	8
2.4	Types of Rainwater Harvesting Tanks, a) Above-ground Storage, and b) Below-ground Storage	11
2.5	Types of Materials, a) Polypropylene Tank, b) Galvanized Sheet Metal Tank, c) Fibreglass Tank, and d) Cast-in-situ Concrete Tank	13
2.6	Super-slim Rainwater Tank	14
2.7	Layout of the Rainwater Harvesting System	16
2.8	a) Velocity Distribution, b) Pressure Distribution, and c) Turbulent Kinetic Energy Distribution in Rainwater Harvesting for 20L/s Pump Flow Rate	17
2.9	VODA Rainwater Harvesting Tank at Kota Kemuning, Shah Alam, Selangor	21
3.1	The Design Options for the Rainwater Harvesting System, a) Design 1, Design 2, and c) Design 3	24

3.2	a) Pipes, b) Balls Types of Animated Flow Results	25
3.3	Flow Chart of Wall-Mounted Rainwater Harvesting Model	26
3.4	Create a New Part for a Single Design Component	27
3.5	Select <i>Top Plane</i> to Create a Sketch	28
3.6	Sketch the Rectangular Base	28
3.7	Edit the Dimensions of the Length and Width	29
3.8	Select the Extrude Function	30
3.9	Extrude the Rectangular Base	30
3.10	Select the Fill Function	31
3.11	Fill the Top Surface of the Tank	31
3.12	Select the Knit Function	32
3.13	Knit All the Surface to Form a 3D Model	32
3.14	Select the Thicken Function	33
3.15	Select the Surface for Thicken	33
3.16	Locate the Circle on Plane	34
3.17	Extrude the Outlet Opening	35
3.18	Completed Storage Tank Model	35
3.19	Form a Straight Line as Path	36
3.20	Adjust the Length of Path Drawn	37
3.21	Form a Circle as Profile	37
3.22	Extrude a Pipeline with Thickness	38
3.23	Select 3D Sketch Option	39
3.24	Form Two Straight Lines with Angle of 90 ° as Paths	39
3.25	Adjust the Length of Path Drawn	40
3.26	Select the Fillet Function	40

3.27	Form a Circle as Profile	41
3.28	Extrude a Joint with Thickness	41
3.29	Select Assembly Function to Assemble all the Parts	42
3.30	Browse for Part	43
3.31	Rotate of Part	43
3.32	Mate the Parts	44
3.33	Start the Flow Simulation Analysis	45
3.34	Setting the Computational Domain to 3D Simulation	46
3.35	Select the Boundary Conditions	46
3.36	Select the Inflow Face	47
3.37	Setting up the Point goals	47
4.1	Technical Drawing for Design 1	50
4.2	Technical Drawing for Design 2	51
4.3	Technical Drawing for Design 3	52
4.4	Developed SWMM Model for Wall-Mounted Rainwater Harvesting System	53
4.5	Prototypes of Wall-Mounted Rainwater Harvesting System, a) Design 1, b) Design 2, and c) Design 3	54
4.6	Streamline Patterns of Scenario 1 with 60mm Pipe, a) Design 1-1, Design 2-1, and Design 3-1	55
4.7	Pressure Zonations of Scenario 1 with 60mm Pipe, a) Design 1-1, Design 2-1, and Design 3-1	55
4.8	Streamline Patterns of Scenario 2 with 90mm Pipe, a) Design 1-2, Design 2-2, and Design 3-2	58

4.9	Pressure Zonations of Scenario 2 with 90mm Pipe, a) Design 1-2, Design 2-2, and Design 3-2	58
4.10	Streamline Patterns of Scenario 3 with 120mm Pipe, a) Design 1-3, Design 2-3, and Design 3-3	61
4.11	Pressure Zonations of Scenario 3 with 120mm Pipe, a) Design 1-3, Design 2-3, and Design 3-3	62

LIST OF ABBREVIATIONS

ARI	-	Average Recurrence Interval
CAD	-	Computer Aided Design
CFD	-	Computational Fluid Dynamics
DID	-	Department of Irrigation and Drainage
MSMA	-	Manual Saluran Mesra Alam
SUDS	-	Sustainable Urban Drainage System
SWMM	-	Stormwater Management Model
WSUD	-	Water Sensitive Urban Design

CHAPTER 1

INTRODUCTION

1.1 Background

Rainwater harvesting is an economic approach of Water Sensitive Urban Design (WSUD) which contains a few simple components to control the stormwater runoff. Basically, the type and size of the rainwater tank are the main considerations of the rainwater harvesting system. Conventional rainwater tank has big capacity which is placed above-ground or underground; but it is space consuming. A wall-mounted tank is introduced here as it could be fitted into urban built environment more adeptly than the conventional rainwater tank. It is installed to the wall of the buildings and it can save the space for other uses.

1.2 Problem Statement

Referring to Figure 1.1, Central City, Kota Samarahan is a modern township that has high density built-up units. Residential and commercial lots alike are designed with limited empty spaces. Therefore, wall-mounted rainwater harvesting tank is an alternative choice for the township. However, this project focuses on commercial lots as the spaces nearby the lot are used for parking lots (Wong, 2015). Normally, wall-mounted rainwater harvesting tank has a smaller capacity if compared to the other conventional storage tanks available in market. Then, multiple tanks can be connected to each others with interconnecting arrangement in order to achieve the desired storage capacity (Tang & Mah, 2015).



Figure 1.1: Selected Commercial Lot is Located at Central City, Kota Samarahan
(<http://wikimapia.org>)

This project is an extension of Wong (2015) which the commercial lot of Central City was taken as the subject of case study. He suggested a series of three tanks would be the most economy against 15 minutes 10-year ARI design storm and the wall-mounted rainwater harvesting tank design is as showed in Figure 1.2 below. The design would be able to reduce the design storm volume by half, meaning half captured and the remaining released for environment flow. The investigation was carried out using the EPA SWMM 5.0 Software (US Environmental Protection Agency-Stormwater Management Model).




Figure 1.2: Design Layout of the Wall-Mounted Rainwater Harvesting Tank for Commercial Lot (Wong, 2015)

The concepts of SWMM are based on rainfall-runoff modelling; in which runoff is generated by rainfall over a catchment, then the runoff is routed through nodes and links until the running water reaching an outlet. In another word, the model is stimulating the volume of water over time over space generally.

However, SWMM lacks the details of the hydraulics. For example, it could not provide whether congestion of flow occurred at the length between the roof and inlet to tank. Besides, overflow pipe that is showed in Figure 1.2 could not be tested for its ease of flow to the stormwater drain. The two design issues highlighted here require detailed modelling. Therefore, this project is intended to go 3D modelling of Wong (2015)'s design to scrutinize the wall-mounted rainwater harvesting system further. A Computational Fluid Dynamics (CFD) modelling using SolidWorks Software is attempted here.

1.3 Objectives

- i. To develop prototypes of wall-mounted rainwater harvesting system by using SolidWorks; and
- ii. To investigate the detailed flow within the wall-mounted rainwater harvesting system by using SolidWorks Flow Simulation.

CHAPTER 2

LITERATURE REVIEW

2.1 Urban Stormwater Management

Nowadays, continuous growth of population, expansion in urbanization, industrialization and irrigated agriculture are the common issues faced by most of the developing countries including Malaysia. There is no denying that urbanization changes the initial hydrology and hydraulic characteristics of catchment with the increment of paved areas (Zakaria, Ab. Ghani, & Chang, 2004). In forested areas, most of the rainfall infiltrates into the soil or trapped by the plants. The topsoil acts as natural temporary water retention media, thus the flooding is less likely to take place in those areas (Yong & Md Nasir, 2004).

In Malaysia, the average yearly rainfall is recorded to be around 3000mm with the average rainfall of 3830mm in Sarawak, 2630mm in Sabah, followed by 2420mm in Peninsular Malaysia (Alnaimi, Murugasen, & Al-Qrimli, 2015). Therefore, the degree of excess runoff generated from developed areas is tremendous as less rainwater infiltrates into the soil. In the past 30 years, rapid urban growth in Malaysia has resulted in increased stormwater flow into receiving waters, thus increasing the flood peaks, and also degrading the water quality (Zakaria et al., 2014). One of the example is the flood occurred at Kuala Lumpur and other states in January 1971 which had caused the loss of properties about RM 200 million and with 61 fatal cases recorded (Takaijudin et al., 2010).

In year 1975, “Planning and Design Procedure No.1: Urban Drainage Design Standard and Procedures” was first established and utilized by the Department of Irrigation and Drainage (DID) (Zakaria et al., 2004). It was a simple standard document

with 10 chapters and had been used as a guideline to design conventional drainage system for more than 25 years since its publication. For this standard, the stormwater management had been practiced where all the surface runoff must be discharged directly to the nearest river or stream in shortest time (Mohd. Sidek et al., 2004). Unfortunately, this practice of rapid disposal and conveyance-oriented approach had caused the occurrence of flash flood and river pollution as well (Zakaria et al., 2004).

In year 2001, a manual which named as Urban Stormwater Management Manual for Malaysia, MSMA had been introduced by DID and widely adopted as a guideline for the development in stormwater management. It consisted of 48 chapters and mainly divided into nine parts such as background information on environmental process and stormwater management, administration aspects and planning processes, detailed information on hydrology and hydraulic, runoff quantity control and conveyance, source and treatment runoff quality controls, runoff quality controls during construction and special stormwater applications as well (DID, 2001). This MSMA manual promoted a more environmentally approach which was known as “control-at-source” approach to minimize the impact of development on stormwater quantity and also water quality control through best management practices (BMPs). Detention or retention facilities were promoted to control the peak and volume of runoff from a given catchment and to reduce the frequency of downstream flooding (refer Figure 2.1).




Figure 2.1: Zero Uncontaminated Discharge Principle (DID, 2001)

By referring to Figure 2.1, the post-development peak flow of runoff must be equal to or less than the pre-development peak flow of runoff as idealized in “zero peak flow contribution” (Zakaria et al., 2004). Besides, the volume of the post-development runoff hydrograph was also required to be reduced to the same volume as the pre-development runoff hydrograph as well. The latter required the retention facilities to retain the different in volume between the post and pre-development hydrograph. In addition, Figure 2.2 shows the suggested measures to achieve the aim of uncontaminated zero peak discharge contribution.




Figure 2.2: Typical Stormwater Management Measures

After ten years, the 2nd Edition of Urban Stormwater Management Manual for Malaysia (MSMA 2nd Edition) had been released in year 2011. It is an improved version of the MSMA 1st Edition to serve as an important guideline to the latest stormwater BMPs (DID, 2011). For MSMA 2nd Edition, there are 20 chapters which cover mainly administration, quantity control design, quality control design, conveyance design, annexure on planting and maintenance (DID, 2011a). In this edition, quality control facilities or BMPs shall be planned and designed to achieve good water quality standards released from completed development project. Besides, stormwater conveyance system shall also be planned and designed based on design storm average recurrence interval (ARIs) to ensure the safety of the public and protection for private and public properties.

2.2 Water Sensitive Urban Design (WSUD)

Urban and industrial developments dramatically alter landscapes from permeable vegetated surfaces to impervious surfaces. The increases in impervious surfaces then increase the rate and volume of stormwater runoff. Therefore, “environmental friendly” approaches should be applied to limit the runoff characteristics after development. This is the new direction for stormwater management system towards sustainable development.

In Malaysia, Urban Stormwater Management Manual for Malaysia (MSMA) has been introduced which associated to the stormwater management system. In other countries, their concept is more or less the same but with different names. For example, United States with Low Impact Development (LID), United Kingdom with Sustainable Urban Drainage System (SUDs), New Zealand with Low Impact Urban Design and Development (LIUDD) and Water Sensitive Urban Design (WSUD) in Australia (Takaijudin et al., 2010).

The term Water Sensitive Urban Design (WSUD) was probably first used in Australia in year 1994 when Whelans presented design guidelines for residential planning and design which are sensitive to the maintenance of the aquatic environment (Wong & Eadie, 2000). In Australia, the philosophy and guiding principles of WSUD were first published in the Water Sensitive Urban Design Guidelines (WSUDG) which