



**EVALUATION AND ANALYSIS ON EXISTING SANITARY LANDFILL'S
LINER AND LEACHATE COLLECTION SYSTEMS**

ADNAN B BAUSAH

This project is submitted in partial fulfillment of
the requirements for the degree of Bachelor of Engineering with Honours
(Civil Engineering)

Faculty of Engineering
UNIVERSITI MALAYSIA SARAWAK
2006

Universiti Malaysia Sarawak

fk

BORANG PENYERAHAN LAPORAN PROJEK TAHUN AKHIR

Judul: EVALUATION AND ANALYSIS ON EXISTING SANITARY LANDFILL'S
LINER AND LEACHATE COLLECTION SYSTEM

SESI PENGAJIAN: 2002-2006

Saya ADNAN B BAUSAH
(HURUF BESAR)

mengaku membenarkan tesis ini disimpan di Pusat Khidmat Maklumat Akademik, Universiti Malaysia Sarawak dengan syarat-syarat kegunaan seperti berikut:

1. Hakmilik kertas projek adalah di bawah nama penulis melainkan penulisan sebagai projek bersama dan dibiayai oleh UNIMAS, hakmiliknya adalah kepunyaan UNIMAS.
2. Naskhah salinan di dalam bentuk kertas atau mikro hanya boleh dibuat dengan kebenaran bertulis daripada penulis.
3. Pusat Khidmat Maklumat Akademik, UNIMAS dibenarkan membuat salinan untuk pengajian mereka.
4. Kertas projek hanya boleh diterbitkan dengan kebenaran penulis. Bayaran royalti adalah mengikut kadar yang dipersetujui kelak.
5. * Saya membenarkan/tidak membenarkan Perpustakaan membuat salinan kertas projek ini sebagai bahan pertukaran di antara institusi pengajian tinggi.
6. ** Sila tandakan (X) di mana kotak yang berkenaan


☐ SULIT

(Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia seperti yang termaktub di dalam AKTA RAHSIA RASMI 1972).

☐ TERHAD

(Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi/badan di mana penyalinannya dijalankan).

☒ TIDAK TERHAD


(TANDATANGAN PENULIS)

Alamat tetap: X 32 Lorong Habib

Abd Rahman Batu 2 Jalan Apas

91000 Tawau

Tarikh: 06 JUN 2006

Disahkan oleh


(TANDATANGAN PENYELIA)

DR. SITI NOOR LINDA BT TAIB


(Nama Penyelia)

Tarikh: 8 JUN 2006

CATATAN * Potong yang tidak berkenaan.
** Jika Kertas Projek ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyertakan sekali tempoh kertas projek. Ini perlu dikelaskan sebagai SULIT atau TERHAD.

APPROVAL SHEET

This project report attached here to, entitled "EVALUATION AND ANALYSIS EXISTING SANITARY LANDFILL'S LINER AND LEACHATE COLLECTION SYSTEMS" prepared and submitted by Adnan Bin Bausah in partial fulfillment of the requirements for the degree of Bachelor of Engineering (Civil) is hereby accepted.



Dr. Siti Noor Linda Taib
Civil Engineering Department
Faculty of Engineering
Universiti Malaysia Sarawak

8 JUN 2006

Date

*For my beloved mother and father
My lovely sister
Ross Azura bt Zahit
Thanks for everything*

ACKNOWLEDGEMENT

Bismillahirrahmannirrahim.

In the name of Allah the Gracious and the Merciful.

First of all, I would like to dedicate my sincere appreciation and gratitude to my supervisor, Dr Siti Noor Linda Taib for her patient assistance, guidance and attention in accomplishing this project.

A very special appreciation to Mr. Henry Sebastian the director of Chemsain Konsultant Sdn. Bhd, Mr. Wong Yih Chung the senior engineering and coordinator of EDS Konsultant Sdn. Bhd and also for Mr. Wee Shin Hee, manager of Tradimas Sdn Bhd. for their support and cooperation in providing information and sharing their experiences and knowledge for this project.

I also would like to express my sincere and earnest appreciation to my parent and family members for their encouragement and endless support. I also want to extend my appreciation to my friends for their help.

Finally, I am very pleased and honored to mention my special thanks to my friends, lecturers and staffs of Faculty of Engineering, Universiti Malaysia Sarawak.

TABLE OF CONTENTS

CONTENT	PAGE
ACKNOWLEDGMENT	i
TABLE CONTENT	ii
LIST OF FIGURE	v
LIST OF TABLE	vi
NOMENCLATURE AND NOTATION	vii
ABSTRAK	x
ABSTRACT	xi
CHAPTER 1 INTRODUCTION	
1.1 General Overview	1
1.2 Major Criteria Discussion	3
1.3 Objective	4
1.4 Scopes Of Study	5
1.5 Summary Of Chapters	6
CHAPTER 2 LITERATURE REVIEW	
2.1 Project Definition	7
2.2 Landfill Sanitary	8
2.2.1 Definition	8
2.2.2 Structure Of Sanitary Landfill	9
2.3 Leachate	11

2.3.1	Definition	11
2.3.2	Factor Effectuated Leachate Composition	14
2.3.3	Leachate Generation	16
2.3.4	Environment And Leachate	18
2.4	Leachate Collection	18
2.4.1	Definition	18
2.4.2	Component Of Leachate Collection	20
2.4.3	General Design Criteria	21
2.4.4	Design Intensity	22
2.5	Liner Of Landfill	22
2.5.1	Definition	22
2.5.2	Liner Material	23

CHAPTER 3 METHODOLOGY

3.1	General	26
3.2	Side Slope Stability Of Liner Structure.	26
3.3	Estimation Of Total Leachate Production	28
3.4	Calculate Leakage Rate	29
3.4.1	Through Geomembrane Liner	29
3.4.2	Through Composite Liner	30
3.5	Internal Drainage Analysis	32

CHAPTER 4 ANALYSIS AND DISCUSSION

4.1	Liner Structure	33
4.1.1	Mambong Sanitary Landfill	33
4.1.2	Bekenu Sanitary Landfill	36
4.2	Side Slope Calculation	43
4.2.1	Side Slope Of Mambong Sanitary Landfill	43
4.2.2	Side-Slope Stability Of Bekenu Landfill.	46
4.3	Leachate Rate Through The Liner	49
4.4	Estimation Of Overall Leachate Production	52
4.4.1	Mambong Sanitary Landfill	52
4.4.2	Bekenu Sanitary Landfill	53
4.5	Estimation Of Pipe Effective Discharge	55
4.6	Leachate Treatment Plant	57
4.6.1	Mambong Sanitary Landfill	57
4.6.2	Bekenu Sanitary Landfill	60
4.7	Discussion	62

CHAPTER 5 CONCLUSION AND RECOMMENDATIONS 69

REFERENCE

APPENDIX

LIST OF FIGURE

FIGURE	PAGE
Figure 2.1 Sanitary Landfill Plan	9
Figure 2.2 Sanitary Landfill Cross Section	10
Figure 4.1 Mambong Center Cross Section	34
Figure 4.2 Bekenu Center Cross Section	37
Figure 4.3 Fabric Separation Layer	38
Figure 4.4 Synthetic As Reinforcement Layer	39
Figure 4.5 Synthetic As Protection Layer	39
Figure 4.6 Examples Of Geomembrane	40
Figure 4.7 Needle Punching On GCL	42
Figure 4.8 Side Slope Of Landfill Liner	43
Figure 4.9 Side Slope Of Landfill Liner	46

LIST OF TABLE

TABLE		PAGE
Table 2.1	Typical Chemical Concentration In Young Leachate	13
Table 2.2	Typical Chemical Concentration In Older Leachate	14
Table 2.3	Potential Health Effect Due To Leachate	19
Table 4.1	Chemical Resistance Of Geomembrane	40
Table 5.1	Comparison Between Geomembrane And TRISOPLAST [®]	64

NOMENCLATURE

BOD	=	Biological Oxygen Demand
BES	=	Bentonite Enhanced Soils
BS	=	British Standard
COD	=	Chemical Oxygen Demand
HDPE	=	High Density Polyethylene
NH ₃ -N	=	Ammonia nitrogen
NO ₃ -N	=	Nitrate nitrogen
Org-N	=	Organic nitrogen
PVC	=	Polyvinylchloride
UV	=	Ultraviolet

NOTATION

a	=	area of single defects
A _g	=	considered geomembrane surface area
A _L	=	area of landfill
A _p	=	area in flow of pipe
B	=	length of rectangular defect

b	=	length of square defect
b_w	=	width of infinitely long
C	=	carbon
cm	=	centimeter
$C_{q0}, C_{q\infty}$	=	Contact quality factor
d	=	diameter of circular defect
F	=	shear force
FS	=	safety factor
g	=	acceleration of gravity
g	=	gram
H	=	hydrogen
h	=	individual lift height of waste
h	=	hydraulic head on top the geomembrane
L	=	liter
m	=	meter
mm	=	millimeter
n	=	Manning's roughness coefficient, $n \approx 0.011$ for HDPE pipe
N	=	nitrogen
N	=	normal force
n	=	number of defects in the geomembrane area
O	=	oxygen
Org	=	organic

P	=	precipitation
q	=	amount of leachate
Q^*	=	leachate rate through infinite long defect
Q_c	=	leachate rate through circular area
Q_p	=	discharge of pipe
Q_r	=	leachate rate through rectangular defect
Q_s	=	leachate rate through square area
R_p	=	hydraulic radius of pipe
s	=	time in second
S_p	=	Slope of the pipe
t	=	thickness of material of liner structure
w	=	individual width of waste
W	=	the weight of lift thickness
β	=	the slope angle
γ	=	unit weight of waste
δ	=	the friction angle between two material
σ	=	strees
σ_{act}	=	actual stress
σ_y	=	yield stress

ABSTRAK

Dalam hierarki pengurusan sampah pepejal daripada kawasan perbandaran dan domestik, pelupusan sampah adalah peringkat yang terakhir. Namun begitu permasalahan sampah pepejal tidak habis dengan tersedianya pusat pelupusan sampah yang dikenali sebagai *Sanitary Landfill*. Sejak akhir-akhir ini negara sering dikejutkan dengan berita pencemaran air yang berpunca daripada air larut resap atau *leachate*. Kaedah pelupusan sisa pepejal yang ideal bukan sahaja memerlukan pelupusan secara fizikal, akan tetapi juga pengurusan air larut resap yang dihasilkan. Air arut lesap merupakan air hujan yang meresapi sisa pepejal terdedah atau yang terletak dalam ruang pelupusan, membawa pelbagai mineral terlarut termasuk bahan kimia dan biologi. Isu-isu pencemaran yang kritikal akan timbul seandainya peresapan larut lesap ini ke dalam tanah tidak disekat dengan baik kerana peresapannya mampu mencemari air bawah tanah seterusnya ke sumber aliran air berhampiran. Kajian ini adalah untuk menilai sejauh mana penggunaan lapisan TRISOPLAST® di Mambong dan lapisan geo-komposit di Bekenu berupaya menghalang peresapan air larut resap ke sumber air bawah tanah. Kajian ini juga turut menilai reka bentuk sistem saliran air larut resap di kedua-dua pusat dan pelan rawatan yang dijalankan. Kajian ini diharap dapat merumuskan persoalan apakah kedua-dua pusat ini mampu beroperasi dengan baik di Malaysia yang menerima taburan hujan yang tinggi setiap tahun atau tidak

ABSTRACT

Waste disposal is the last stage in the hierarchical of a municipal waste management. However, solid waste problems do not end with the application of Sanitary Landfill in the waste disposal. Currently, the burning news of water pollution sources from leachate had spread nationwide. The ideal procedure of solid waste disposal does not only involve the physical management of waste but also the management of leachate. Leachate is rain water absorbed into waste which then carries dissolved mineral including chemical, biological and other substances. The issues of pollution can be critical if leachate is not properly blocked from entering into the soil as it can pollute the underground water and nearby water resources. This study was conducted to investigate the effectiveness of using the TRISOPLAST® layer in Mambong and geo-composite layer, in Bekenu to prevent the absorption of leachate into the underground water. This study also investigates the design of the leachate channel system and the treatment plan for both sites. This study would be able to determine whether both centres can operate efficiently or not in Malaysia where heavy rainfall is received annually.

CHAPTER 1

INTRODUCTION

1.1 General Overview

Sanitary landfill is a system for managing solid waste. The basic of this system was introduced in 1500 B.C at Greek-city state of Athens. The laws state that the waste must be located far away from the gates of the city with the distance of not less than 1 mile.

Fulfillment of landfill sanitary is very important for this moment. The need is parallel to the addition of population of society and industrial growth. Sanitary landfill is one of the solutions to overcome waste problem besides reuse and

recycling campaign. To add, sanitary landfill may have a live span more than estimated if the recycling program succeeds in reducing volume of waste.

Sanitary landfill is a combination of several technologies from several disciplines. Although this system has a risk due to the possibility of water pollution caused by infiltration of leachate into the ground water resource, landfill still applies even in modern countries.

The government or private agencies that are involved in the waste management are only developing this system in the big city because of the cost, technologies limitation and the area's requirements. Two (cost and technologies) of these three elements are also the requirements needed to achieve zero problems in this system.

In Malaysia, including Sarawak, sanitary landfill is applied to overcome solid waste problem. Many actions have been taken by the State Government and the company or organization to reduce problem involving landfill including application of latest technology.

1.2 Major Criteria Discussions

There are two main criteria to consider in this study. First, the liner construction and the second one is the leachate collection. A landfill liner is the most important part in a landfill construction. It has a function to avoid water pollution due to leachate. The liner material must be able not to allow the leachate to infiltrate the soil under the liner structure, which then enters the groundwater sources. The infiltration of leachate to the ground water makes the water unsafe to the public. Thus, the liner must be able to contain and has the ability to stop leachate infiltration.

Leachate that is produced in the landfill site consists of chemical and biological components, is collected from the bottom of the landfills by a series of collection pipes installed into the base of the landfill. The leachate percolates through the waste and enters into the pipes where it collects.

Leachate managing plant includes the collection and removal of the leachate from the dumpsite and the treatment process. There are many methods to apply in managing the leachate and each method has its own advantage respectively. Some method is useful in one aspect but not efficient if applied in another aspect. Because of this reason, the selection of technology is done after considering many criteria.

1.3 Objective

The determination of municipal agency in Kuching and Miri areas to apply the sanitary landfill as the alternative way to manage the solid waste is a right decision. This will reduce the solid waste problem rising from community around residence area in these mushrooming cities I Sarawak. Sanitary landfill replaces old method to disposal of waste.

The existing sanitary landfill in Mambong uses technology from Germany in its liner construction. Besides that, the drainage system designs for the landfill also become the interests in this investigation. This landfill project consists of a few new imported technologies that are firstly applied in South East Asia region. Its success in reducing solid waste problem is expected to will be followed by other countries.

The questions are how effective is the use of sanitary landfill's liner and leachate collection systems in our country (tropical country) and what are the steps done to avoid the problem due to leachate? The main objective of this Final Year Project is to investigate the liner construction and leachate collection in landfill. These two elements are the main factor to consider that leachate from landfill is not a peril to the environment.

1.4 Scope of Study

Landfill sanitary is one field that is too wide to discuss. To achieve the objective of this Final Year Project, the study is just to spot the related element of sanitary landfill. The followings are the main topic that will be discussed:

Find out the meaning of landfill sanitary elements. It is important to know what the definition of terms used in sanitary landfill operation. Progress of study will be smooth if the right terms are known.

This study also looks out the main structure of landfill sanitary in term of liner and drainage. The purpose of each element and the material used in construction are studied.

Besides that, the discussions include analysis on the type of material and the suitability to use it in our country. Because a lot of technologies that have been applied are imported, so a task in this project to observe the suitability of the element.

Finally, is the study on leachate. What its component, why is it hazard to the environment and what are the steps performed to reduce the risk. Other topics which influence leachate are also discussed.

1.5 Summary of Chapters

Summary of the whole topic by chapter are explains below:

Chapter 2 is literature review. This chapter will discuss about project definition, sanitary landfill, structure of sanitary landfill, factor effected leachate composition, leachate generation, environmental and leachate, leachate collection, component of leachate collection, general design criteria, design intensity, liner of landfill and liner material.

Chapter 3 is methodology. This chapter discuss about side slope stability of liner structure, estimation of total leachate production, calculate leakage rate through liner and internal drainage analysis.

Chapter 4 is analysis and discussion. This chapter is analyzed and discuss of the liner and leachate collection of landfill in both of landfill case study.

Chapter 5 is conclusion and recommendation. Some conclusion and recommendation from the analysis are listed in this chapter.

CHAPTER 2

LITERATURE REVIEW

2.1 Project Definition

This final year project is entitled Evaluation And Analysis On Existing Sanitary Landfill's Liner Construction And Leachate Collection Systems. The existing landfill in Sarawak state are in Mambong in Kuching that uses application of new advanced technology to manage the dumpsite area and in Miri that use the different method in terms of liner construction and material and leachate treatment plants.

2.2 Sanitary Landfill

2.2.1 Definition

Sanitary landfill is defined as a land disposal site employing an engineered method of disposing of solid wastes on land in manner that minimizes environmental hazards by spreading the solid wastes to the smallest practical volume, and applying and compacting cover material at the end of each day (Chow et al., 1988)

In developing and managing sanitary landfill some elements need to be considered, such as legal requirement, cooperation between two or more municipalities, social and political aspects and long term planning. These elements are very important to achieve high quality in managing solid wastes.

Generally there are two basic methods involved in constructing sanitary landfill. Area method and trench method, where many sites apply both either simultaneously or sequentially.

Solid waste is disposed on site surface, compacted, and then covered daily with soil. This is called area method. Different to trench method, waste is placed in trench and compacted. The use of any of the method depends on the site condition.

Usually the area method is applied if the site is flat or rolling terrain and canyons. The disadvantage of this method is the cover material is from off site which will increase the cost. The trench method is used on level or gentle sloping land where the water table is not high. The cover material found from on site (result of excavated site).

2.2.2 Structure of Landfill

Sanitary landfill is made up of five major components such as a liner system, storage space for placing the waste that is usually arranged in cells, a leachate collection system, a gas collection system and cover or capping. Figure 2.1 and figure 2.2 are the sanitary landfill top view and the fundamental cross section of landfill.



Figure 2.1 Sanitary Landfill Top View