## A Wireless Based StormPAV Green Pavement Moisture Monitoring System

Publisher: IEEE





J. Annisa: L. C. Eng: N.T. Razali: D.Y.S. Mah: M.A. Mannan All Authors















## More Like This

Application of Chemical Grouting Method in Settle Down Disengaging of Cement Concrete Slab 2012 International Conference on Computer Distributed Control and Intelligent Environmental Monitoring Published: 2012

RF moisture measurement of concrete with a resonator sensor

2012 22nd International Crimean Conference "Microwave & Telecommunication Technology" Published: 2012

Show More



## Abstract

**Document Sections** 

I Introduction

II. Methodology

III. Design and Implementation

IV. Results and Discussion

V. Conclusion

Authors

**Figures** 

References

Keywords

Metrics

Abstract:

Concrete provides the foundation for the key systems in most construction projects mainly roads and buildings. For concrete, water is a key ingredient in the hydration process that sets and cures the cement portion of any concrete blend. However, if the excess water or moisture content is not given time to leave the slab, it will cause damage. This research focused on developing a moisture sensor monitoring system for StormP A V green pavement concrete which uses wireless data transfer to the processor. The monitoring system used Arduino as its operating system, dielectric constant concept to monitor the moisture content of the concrete, XBEE Pro as a tool for wireless data transfer, and Node RED software for data collection, monitoring, and analysis. Control experiment was carried out to determine the suitable method for measuring the moisture of the concrete. From the control experiment, it was convinced that the moisture content of the concrete could be determine by its dielectric constant. The performance of this developed system was validated by observing ten samples of freshly form concrete. It was found that the average days for the concrete to be completely dry which is on the 19th to 20th day. This proved that the time to wait before curing could be shortened to increase the productivity for concrete production rather than using the conventional estimation curing period which had been practiced formerly. Thus, the developed moisture sensor monitoring system which utilized low cost materials, low technological complexity, wireless data transfer and also sufficient sensitivity can be employed in concrete industry in wide-ranging.

Published in: 2019 2nd International Conference on Applied Engineering (ICAE)

Date of Conference: 2-3 Oct. 2019

Date Added to IEEE Xplore: 13 October 2020

ISBN Information:

INSPEC Accession Number: 20053773

DOI: 10.1109/ICAE47758.2019.9221722

Publisher: IEEE