

Article

Structural, Electromagnetic and Microwave Properties of Magnetite Extracted from Mill Scale Waste via Conventional Ball Milling and Mechanical Alloying Techniques

Madiha Fathi Elmahaishi ¹, Raba'ah Syahidah Azis ^{1,2,*} , Ismayadi Ismail ² , Muhammad Syazwan Mustaffa ², Zulkifly Abbas ¹, Khamirul Amin Matori ^{1,2}, Farah Diana Muhammad ¹, Nor Kamilah Saat ¹, Rodziah Nazlan ³ , Idza Riati Ibrahim ⁴, Nor Hapishah Abdullah ⁵ and Nurhidayat Mokhtar ¹

- ¹ Department of Physics, Faculty of Science, University Putra Malaysia (UPM), Serdang 43400, Selangor, Malaysia; gs57071@student.upm.edu.my (M.F.E.); za@upm.edu.my (Z.A.); khamirul@upm.edu.my (K.A.M.); farahdiana@upm.edu.my (F.D.M.); kamilah@upm.edu.my (N.K.S.); hidayat@upm.edu.my (N.M.)
- ² Materials Synthesis and Characterization Laboratory (MSCL), Institute of Nanoscience and Nanotechnology (ION2), Universiti Putra Malaysia (UPM), Serdang 43400, Selangor, Malaysia; ismayadi@upm.edu.my (I.I.); mm_syazwan@upm.edu.my (M.S.M.)
- ³ Faculty of Industrial Sciences, Technology Universiti Malaysia Pahang (UMP), Lebuhraya Tun Razak, Gambang 26300, Pahang, Malaysia; rodziah@ump.edu.my
- ⁴ Centre For Pre-University Studies, Universiti Malaysia Sarawak (UNIMAS), Kota Samarahan 94300, Sarawak, Malaysia; iiriati@unimas.my
- ⁵ Functional Devices Laboratory (FDL), Institute of Nanoscience and Nanotechnology (ION2), Universiti Putra Malaysia (UPM), Serdang 43400, Selangor, Malaysia; hapishah@upm.edu.my
- * Correspondence: rabaah@upm.edu.my; Tel.: +603-9769-6666



Citation: Elmahaishi, M.F.; Azis, R.S.; Ismail, I.; Mustaffa, M.S.; Abbas, Z.; Matori, K.A.; Muhammad, F.D.; Saat, N.K.; Nazlan, R.; Ibrahim, I.R.; et al. Structural, Electromagnetic and Microwave Properties of Magnetite Extracted from Mill Scale Waste via Conventional Ball Milling and Mechanical Alloying Techniques. *Materials* **2021**, *14*, 7075. <https://doi.org/10.3390/ma14227075>

Academic Editor:
Jose Antonio Alonso

Received: 30 September 2021
Accepted: 9 November 2021
Published: 22 November 2021

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2021 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

Abstract: This study presents the utilization of mill scale waste, which has attracted much attention due to its high content of magnetite (Fe₃O₄). This work focuses on the extraction of Fe₃O₄ from mill scale waste via magnetic separation, and ball milling was used to fabricate a microwave absorber. The extracted magnetic powder was ground-milled using two different techniques: (i) a conventional milling technique (CM) and (ii) mechanical alloying (MM) process. The Fe₃O₄/CM samples were prepared by a conventional milling process using steel pot ball milling, while the Fe₃O₄/MM samples were prepared using a high-energy ball milling (HEBM) method. The effect of milling time on the structural, phase composition, and electromagnetic properties were examined using X-ray diffraction (XRD) and a vector network analyzer (VNA). XRD confirmed the formation of magnetite after both the magnetic separation and milling processes. The results revealed that Fe₃O₄ exhibited excellent microwave absorption properties because of the synergistic characteristics of its dielectric and magnetic loss. The results showed that the Fe₃O₄/CM particle powder had a greater absorption power (reflection loss: <−10 dB) with 99.9% absorption, a minimum reflection loss of −30.83 dB, and an effective bandwidth of 2.30 GHz for 2 mm thick samples. The results revealed the Fe₃O₄/MM powders had higher absorption properties, including a higher RL of −20.59 dB and a broader bandwidth of 2.43 GHz at a matching thickness of only 1 mm. The higher microwave absorption performance was attributed to the better impedance matching property caused by the porous microstructure. Furthermore, the magnetite, Fe₃O₄ showed superior microwave absorption characteristics because of the lower value of permittivity, which resulted in better impedance matching. This study presents a low-cost approach method by reutilizing mill scale waste to fabricate a high purity crystalline Fe₃O₄ with the best potential for designing magnetic nano-sized based microwave absorbers.

Keywords: magnetite (Fe₃O₄); mill scale; conventional milling (CM); mechanical alloying milling (MM); microwave; electromagnetic properties

1. Introduction

Microwave absorbing materials (MAMs) are materials that can interact with electromagnetic (EM) waves and dissipate into other forms of thermal energy through their electric