

FLASH FLOOD MONITORING AND WARNING SYSTEM

Ho Wan Yu

Bachelor of Computer Science with Honours

(Network Computing)

FLASH FLOOD MONITORING AND WARNING SYSTEM

HO WAN YU

This project is submitted in partial fulfilment of the requirements for the degree of Bachelor of Computer Science With Honours

(Network Computing)

Faculty of Computer Science and Information Technology

UNIVERSITI MALAYSIA SARAWAK

UNIVERSITI MALAYSIA SARAWAK

THESIS STATUS ENDORSEMENT FORM				
TITLE Flash F		Flood Monitoring and	d Warning System	
	ACAL	DEMIC SESSION: _	2019/2020	
		HO WAN		
		(CAPITAL LET	TERS)	
	-	hall be kept at the Centre following terms and cond	e for Academic Information Services, Universiti litions:	
 The Thesis is solely owned by Universiti Malaysia Sarawak The Centre for Academic Information Services is given full rights to produce copies for educational purposes only 				
3.			s given full rights to do digitization in order to	
4.5.	as part of its exchange item program between Higher Learning Institutions [or for the purpose of interlibrary loan between HLI]			
	CONFIDENTIAL	(Contains classified info	ormation bounded by the OFFICIAL SECRETS	
	RESTRICTED		ormation as dictated by the body or organization	
✓	where the research was conducted) UNRESTRICTED			
	1 90		Validated by	
(AUTI	(AUTHOR'S SIGNATURE)		(SUPERVISOR'S SIGNATURE)	
Permanent Address				
Tamar	alan Chempedak, n Gopeng, Gopeng, Perak.			
Date:	22 July 2023		Date:	

Note * Thesis refers to PhD, Master, and Bachelor Degree

^{**} For Confidential or Restricted materials, please attach relevant documents from relevant organizations / authorities

DECLARATION

I hereby state that this project and all of its contents are my original creation, with the exception of the information that has been mentioned and quoted, which has been taken from other sources and referenced.



22 JULY 2023

ACKNOWLEDGMENT

In this project, I would like to acknowledge and give my warmest thanks to my supervisor Dr. Lau Sei Ping who make this Final Year Project on the topic Flash Flood Monitoring and Warning System possible. I feel myself very fortunate to have such a thoughtful and professional supervisor like him. I was able to complete all my project stages thanks to his direction and counsel.

Besides, I would like to thank my Final Year Project partner, Christopher Sii How Chiong, who handled the configuration of the Flash Flood Observer and developed the mobile application for admin's features. Christopher consistently engaged in discusses and collaborated closely with me to sort out the issues we had throughout our project. Last but not least, I would also like to deliver my thankfulness to my family and friends for their continuous support through the journey to complete my Final Year Project within the time given.

ABSTRACT

Flood is natural disaster that will cause a significant damage to the environment and both living and non-living things. Kota Samarahan repeatedly experienced flooding due to few reasons such as low-lying area, gradual urbanisation, and no masterplan to construct the drainage system. These issues become a big problem when the flash flood is happened and will interrupt society's activities. Therefore, the real-time flash flood monitoring and warning system is proposed in this project. The concept of this proposed system is to share the water level reading from the hardware. The hardware, Flash Flood Observer is under other FYP project to collect the data to the same sharing database server. The proposed system able to share the real-time water level and show the flood prone area based on the sea level using the GIS map. When the water level reaches a critical level, it will broadcast the warning to the enduser. This project is developed based on Rapid Application Development (RAD). The methodology used as the methodology offers a rapid prototype and iterative delivery as software development.

ABSTRAK

Banjir adalah bencana semula jadi yang akan menyebabkan kerusakan yang besar kepada persekitaran dan benda-benda hidup dan bukan hidup. Kota Samarahan kerap mengalami banjir disebabkan oleh beberapa sebab seperti kawasan rendah, urbanisasi beransur-ansur, dan tiada pelan induk untuk membina sistem saliran. Isu-isu ini menjadi masalah besar apabila banjir kilat berlaku dan akan menganggu aktiviti masyarakat. Oleh itu, sistem pemantauan dan amaran banjir kilat masa nyata diusulkan dalam projek ini. Konsep sistem yang diusulkan adalah untuk berkongsi bacaan aras air dari perkakasan. Perkakasan, Flash Flood Observer adalah di bawah projek FYP yang lain untuk mengumpul data kepada pangkalan data yang sama. Sistem yang diusulkan boleh berkongsi aras air masa nyata dan menunjukkan kawasan berisiko banjir berdasarkan aras laut menggunakan peta GIS. Apabila aras air mencapai tahap kritikal, ia akan menyiarkan amaran kepada pengguna akhir. Projek ini dibangunkan berdasarkan Pembangunan Aplikasi Pantas (RAD). Metodologi yang digunakan sebagai metodologi menawarkan prototaip pantas dan penghantaran iteratif sebagai pembangunan perisian.

Table of Contents

DECLARATION	I
ACKNOWLEDGMENT	II
ABSTRACT	III
ABSTRAK	IV
LIST OF FIGURES	IX
LIST OF TABLES	XIII
CHAPTER 1: INTRODUCTION	1
1.1 Introduction/Background	1
1.2 Problem Statement	2
1.3 Objectives	2
1.4 Project Scope	2
1.5 Brief Methodology	3
1.6 Significance of Project	5
1.7 Project Schedule	5
1.8 Expected Outcome	6
1.9 Project Outline	7
1.9.1 Introduction	7
1.9.2 Literature Review	7
1.9.3 Requirement Analysis and Design	7
1.9.4 Implementation and Testing	7
1.9.5 Conclusion and Future Works	8
CHAPTER 2: BACKGROUND & LITERATURE REVIEW	9
2.1 Introduction	9

2.2 Review on Existing System	9
2.2.1 FloodAlert	9
2.2.2 PegelAlarm: Water level alerts	11
2.2.3 MyPublic InfoBanjir	13
2.3 Comparison between Three Reviewed Systems	17
2.4 Direction of Proposed System	18
2.5 Summary	20
CHAPTER 3: REQUIREMENT ANALYSIS AND SYSTEM DESIGN	21
3.1 Introduction	21
3.2 Requirement Analysis	21
3.2.1 User Requirements	22
3.2.2 System Requirements	22
3.3 System Design	25
3.3.1 Flowchart	25
3.3.2 Context Diagram	28
3.3.3 Data Flow Diagram (DFD) Level 0	29
3.3.4 Entity Relationship Diagram (ERD)	32
3.3.5 System Architecture	37
3.3.6 User Interface Design	38
3.4 Summary	43
CHAPTER 4: IMPLEMENTATION	44
4.1 Installation and Configuration	44
4.1.1 Heroku	44
4.1.2 ClearDB MySQL	44
4.1.3 GitHub	45

4.1.4 Visual Studio Code with Flutter	45
4.1.5 Google Earth Pro	47
4.1.6 ArcGIS Pro	48
4.2 Implementation on The Proposed System	48
4.3 Mobile Application Implementation	48
4.3.1 Function of Each Module in Flash Flood Monitoring and Warning System	ı 49
4.3.1.1 User Registration	49
4.3.1.2 User Login	50
4.3.1.3 User Logout	51
4.3.1.4 View Station	53
4.3.1.5 View Dashboard	55
4.3.1.6 Add Monitoring Station	57
4.3.1.7 View Monitoring Station	60
4.3.1.8 Update Monitored Station	61
4.3.1.9 Delete Monitored Station	63
4.3.1.10 View Flood Map	65
4.3.1.11 Receive Notification	75
4.4 Summary	79
CHAPTER 5: TESTING	80
5.1 Introduction	80
5.2 Functional Testing	80
5.2.1 Unit Testing	80
5.2.2 System Testing	90
5.3 Non-Functional Testing	91
5 4 Summary	92

CHAPTER 6: CONCLUSION AND FUTURE WORK	93
6.1 Introduction	93
6.2 Project Achievement	93
6.3 Project Limitations	94
6.4 Future Works	94
6.5 Summary	94
Reference	96

List of Figures

Figure 1.1. Software Life Cycle of Rapid Application Development (Kissflow, 2022)
Figure 1.2. Project Schedule and Gantt Chart6
Figure 2.1. Workflow of FloodAlert
Figure 2.2. Flood Mapping feature able to discover flood prone areas
Figure 2.3. Workflow of PegelAlarm
Figure 2.4. Alert setting can configure based on individually defined threshold level
Figure 2.5. Workflow of MyPublic InfoBanjir14
Figure 2.6. Water level and rainfall graph recorded in the application
Figure 2.7. Classification of water level (Adapted from Department of Irrigation and Drainage
2020)
Figure 3.1. Flowchart of the Flash Flood Observer and Flash Flood Monitoring and Warning
System
Figure 3.2. Context diagram for Flash Flood Monitoring and Warning System28
Figure 3.3. DFD Level 0 for Flash Flood Monitoring and Warning System
Figure 3.4. DFD Level 1 for Process 6.0 in Flash Flood Monitoring and Warning System 31
Figure 3.5. DFD Level 1 for Process 9.0 in Flash Flood Monitoring and Warning System 32
Figure 3.6. Entity Relationship Diagram (ERD) of Flash Flood Monitoring and Warning
System
Figure 3.7. System architecture of Flash Flood Monitoring and Warning System
Figure 3.8. Registration page of Flash Flood Monitoring and Warning System
Figure 3.9. Login page of Flash Flood Monitoring and Warning System
Figure 3.10. Main page of Flash Flood Monitoring and Warning System
Figure 3.11. Add station page in Flash Flood Monitoring and Warning System

Figure 3.12. Main page after added station of Flash Flood Monitoring and Warning	-
Eigen 2.12 Manitoring Station many of Elech Elech Manitoring and Warning St	
Figure 3.13. Monitoring Station page of Flash Flood Monitoring and Warning Sy	
collaboration with Christopher	41
Figure 3.14. Dashboard page of Flash Flood Monitoring and Warning System	41
Figure 3.15. Notification page of Flash Flood Monitoring and Warning System	42
Figure 3.16. Setting page of Flash Flood Monitoring and Warning System	42
Figure 3.17. Account page of Flash Flood Monitoring and Warning System	43
Figure 4.1. Heroku dashboard	44
Figure 4.2. ClearDB MySQL tables	45
Figure 4.3. GitHub dashboard	45
Figure 4.4. VS Code Official Website	46
Figure 4.5. Flutter Official Website	46
Figure 4.6. Environment variable path setup	47
Figure 4.7. Google Earth Pro Official Website	47
Figure 4.8. ArcGIS Pro Official Website	48
Figure 4.9. Registration page of Flash Flood Monitoring and Warning System	50
Figure 4.10. Login page of Flash Flood Monitoring and Warning System	51
Figure 4.11. Logout page of Flash Flood Monitoring and Warning System	52
Figure 4.12. Logout alert dialog of Flash Flood Monitoring and Warning System	52
Figure 4.13. Station page of Flash Flood Monitoring and Warning System	53
Figure 4.14. Code Snippet of PHP script water level classification	54
Figure 4.15. Flutter code of view station	55
Figure 4.16. View Dashboard page	56

Figure 4.17. Source code of retrieving and parsing data from server to Dashboard page	57
Figure 4.18. Add Station page	58
Figure 4.19. Drop-down menu to add the monitoring station	58
Figure 4.20. Flutter code for adding monitoring station	59
Figure 4.21. PHP Backend Script for adding monitoring station	60
Figure 4.22. View Monitored Stations	60
Figure 4.23. Flutter code for fetching user station	61
Figure 4.24. PHP Backend Script for fetching user station	61
Figure 4.25. Update Monitored Station	62
Figure 4.26. Flutter code for updating user station	62
Figure 4.27. PHP Backend Script for updating user station	63
Figure 4.28. Delete monitored station	64
Figure 4.29. Flutter code for deleting user station	64
Figure 4.30. PHP Backend Script for deleting user station	65
Figure 4.31. Add marker on Flood Map	65
Figure 4.32. Flutter code for adding marker on Flood Map	66
Figure 4.33. Draw a path of the station area	67
Figure 4.34. Save the file type as .Kml	67
Figure 4.35. Convert the KML to GPX format	68
Figure 4.36. GPX to Features	69
Figure 4.37. Kriging of the station area	69
Figure 4.38. Coordinate of the station	70
Figure 4.39. Contour of the station area based on the kriging	71
Figure 4.40. Colour classification for each group of values	71

Figure 4.41. Draw the polygon of the flood prone areas	72
Figure 4.42. Polygon coordinate of the flood prone area	72
Figure 4.43. Load polygons for each station	73
Figure 4.44. Show flood prone area when station in Danger level	74
Figure 4.45. Track the current position of the device	75
Figure 4.46. Toggle to display the flood prone areas	75
Figure 4.47. Flutter code to receive the notification	77
Figure 4.48. Flutter code to fetching the notification data	78
Figure 4.49. Notification Page	79
Figure 5.1. Flash Flood Observer implemented by Christopher Sii How Chiong	90
Figure 5.2. Testing for receiving notifications	91

List of Tables

Table 2.1. Each of the description of the water level (Adapted from Department of Irr	rigation
and Drainage, 2020)	16
Table 2.2. Comparison between three reviewed systems	17
Table 3.1. Hardware requirements for development of Flash Flood Monitoring and V	Varning
System	23
Table 3.2. Software requirements for development of Flash Flood Monitoring and V	Varning
System	24
Table 3.3. user table	34
Table 3.4. setting table	34
Table 3.5. user_station table	34
Table 3.6. user_notification table	35
Table 3.7. admin table	35
Table 3.8. sensor_device table	35
Table 3.9. sensor_reading table	35
Table 3.10. station table	36
Table 3.11. adminnotification table	36
Table 3.12. fcm_tokens table	36
Table 3.8. User interface design for mobile application	38
Table 5.1. Test Case for Registration page	81
Table 5.2. Test Case for Login and Logout page	82
Table 5.3. Test Case for Station Page and Dashboard Page	83
Table 5.4. Test Case for Add Monitoring Station	84
Table 5.5. Test Case for Update Monitoring Station	85

Table 5.6. Test Case for Delete Monitoring Station	86
Table 5.7. Test Case for Map Page	87
Table 5.8. Test Case for Notification page	89
Table 5.9. Non-functional testing	91
Table 6.1. Achievements of project objectives in Flash Flood Monitoring and	Warning System
	93

CHAPTER 1: INTRODUCTION

1.1 Introduction/Background

Floods are mostly caused by geographical conditions, metrological conditions, hydrological conditions, flaws with planning, and environmental conditions brought on by human activities etc. (Priyadarshinee et al., 2015). Floods can have disastrous repercussions on people, the environment, and the economy. It became a trouble when the homes, bridges, roads, and automobiles are all ruined by flooding, especially flash floods. When floods strike, the ecology also suffers (Almawgani, 2020). There are many flood detection systems still using the traditional method of disaster forecasting in rural areas in Malaysia. The traditional method which locals keep an eye on water rises that occur close to rivers. This action is too dangerous since the region close to the river has become unsafe for their safety, which restrict current water level data from being gathered causing delay in broadcast the notification to the locals (Priyadarshinee et al., 2015). The current flood detection system only keeps track of the water level, but it does not offer a reliable warning system to the local community.

This work focuses on designing and developing of a Flash Flood Monitoring and Warning System by applying IoT device, "Flash Flood Observer". The "Flash Flood Observer" created by one of the FYP students (SEM 1 2022/2023), Christopher Sii How Chiong (69385), which will collect all the data of water level then transmitted and stored on a same sharing database server. The Flash Flood Monitoring and Warning System will retrieve and process the water level data into information from the database server for forecasting and issuing push notification to local community or driver that installed the application on the smartphone. The GIS map also be implemented in the system where the map will be updated by overlaying flood prone area on the map of the possible affected area with reference to the threshold water level.

1.2 Problem Statement

Flood is a natural disaster that affects both living and non-living things in the environment. According to the Senior Minister of Works (MoW) Dato Sri Fadillah Yusuf, Kota Samarahan frequently experienced flooding because of low-lying area, gradual urbanisation, and no masterplan to construct or upgrade the drainage system (Nur Ashikin Louis, 2021). These natural calamities become a big problem when safe zones, and other critical information cannot be noticed by local community and the drivers to assist in disaster preparedness and response. Hence, this problem interrupts society's activities such as local community or the drivers not aware of the flash flood happening in far distance. In these conditions, real time flood warning system is important because flood can happen when everyone is resting thus may not be aware of the rising water until it is too late.

1.3 Objectives

The following are the project objectives:

- To design an online system for storing water level information relayed from the "Flash Flood Observer".
- To provide real-time water level conditions in normal, alert, warning, and danger.
- To broadcast a location-aware flood warning to the local community through the mobile application.

1.4 Project Scope

The scope of the project are focusing on allowing the passing of the water level reading from the hardware. The hardware development, Flash Flood Observer is under other FYP project which is handled by Christopher Sii How Chiong. The Flash Flood Observer will post the water level data collected to the same sharing database server. With all the water level readings, the

flash flood monitoring and warning system can predict when the water level reaches a critical level. Besides, the warning system able to show the affected area based on the sea level. With this information, the system will broadcast the warning to the end-user. This system is designed and developed for Android-based smartphone users using the Flutter with Visual Studio Code. The target user of this Flash Flood Monitoring and Warning System app are the local community and the driver.

1.5 Brief Methodology

The selected methodology for the Flash Flood Monitoring and Warning System is Rapid Application Development (RAD). This is because RAD life cycle provides higher efficiency for rapid development. RAD is a reduction in planning and requirement analysis but more focus on rapid prototyping. Besides, RAD uses a shorter time to complete and able to produce more quality project with limited manpower.

Rapid Application Development (RAD)




Figure 1.1. Software Life Cycle of Rapid Application Development (Kissflow, 2022)

Phase 1: Requirement Planning

During this phase, gathering the requirements that are faced by the user which are related to the flash flood happening. Developer needs to consider the requirements of the user and the problem statement. Once the requirement is figured out, the estimated project timeline will be outlined.

Phase 2: User Design

Once the project has been scoped, the user interface will begin to design and build out the initial prototypes. The goal in this phase is to rapidly produce a working design and at the same time can meet the user experience. The prototype design is implemented and able to share the water level information and broadcast the location aware alert to the user. After demonstration to the user, the prototype will be tested and improved in turn based on the requirements until all the requirements have been met.

Phase 3: Construction

In this phase, all the requirement, design and feature of the application will be converting into source code. Since most of the user problems and changes during the iterative prototyping phase, this phase able to construct a final working model faster. The warning system is thoroughly tested during this phase to ensure the result satisfies user expectations and objectives. At the same time, the working prototype of the warning system will be built and improved.

Phase 4: Cutover

The final phase is ready to implementation the completed and refined warning system after approval by the user and the final product is ready to release.

1.6 Significance of Project

The propose of this system is help the local community to acknowledge the current flood water level of the user location and able to help the driver aware the flash flood happening in far distance. The system with the GIS map able to display and provide real-time water level conditions in normal, alert, warning, danger level. Besides, this proposed system able to help the local community or the driver to face or avoid the disaster as the system will broadcast alert to the end-user in real-time regarding the water level danger where the flood is occurring. In this project, the proposed system uses the water level data collected from "Flash Flood Observer", and based on the water level data to determine whether there is a potential flood.

1.7 Project Schedule

Project schedule is used as progression guidance for the project. Figure 1.2 shows the project schedule and Gantt Chart as a timeline progress of the Final Year Project 1 and 2.




Figure 1.2. Project Schedule and Gantt Chart

1.8 Expected Outcome

At the end of the project, the real-time flash flood monitoring and warning system by applying IoT device will be designed and developed. The expected outcome of this projects is the system

able to accept and store the water level information for the observer to monitor and share the information of forecasting flood events in real time. The system will be able to monitor the current flood water level, able to show the flood prone area and enable broadcast location aware flood warning regarding the water danger level settings.

1.9 Project Outline

The project report consists of five chapters as described below:

1.9.1 Introduction

Chapter 1 describes about the general introduction of the proposed system. This chapter consists of the background, problem statements, objectives, project scope, brief methodology used, significance of project, project schedule and the expected outcome of the project.

1.9.2 Literature Review

In this chapter, literature review of reviewed systems will be selected through the existing systems and related paper. The reviewed systems will be discussed and compared, as well as describing the proposed system. The technology and software development tools utilised to create the proposed system are also reviewed in this chapter.

1.9.3 Requirement Analysis and Design

Chapter 3 discusses the system architecture and the methodology used in this proposed system. Rapid Application Development (RAD) is chosen due to its efficiency. It has four phases in RAD which is requirement planning, user design, construction, and cutover. In RAD, it more focuses on the prototype over planning. These four phases of RAD methodology will be discussed in detail in this chapter.

1.9.4 Implementation and Testing

Chapter 4 discusses the implementation phase and the testing phase done in this project. The system prototype is developed according to the system design and conduct the testing. Besides,