

Relationship Performance of Cylindrical Detention Pond (CDP) as Depression Storage and Runoff Reduction Under Fully Saturated Condition

H. Maseri*, O. S. Selaman, M. A. Mannan, and S. N. L. Taib

Department of Civil Engineering, Faculty of Engineering, Universiti Malaysia Sarawak (UNIMAS), 94300 Kota Samarahan Sarawak, Malaysia

Permeable pavements are a key Storm water management measure employed both to attenuate surface runoff in urban areas and to filter urban storm water pollutants. Existing permeable pavements (PP) are design with the specific percentage porosity whereby enabling excess rainwater to infiltrate through the system and acting as a depression storage at the same time. Depression storage basically refers to the volume of water trapped in the depression when the precipitation of a storm reaches the ground and filled up all the depression before it can flow over the surface. Cylindrical Detention Pond (CDP) is an alternative paving material that may alleviate many of the hydrological problems caused by urban runoff from developed areas. CDP consist of three basic component; top cover, bottom cover and hollow cylindrical at centre (300 mm thickness). The hollow cylindrical has approximate 50 percent porosity from the total solid of component, which is every 1 inch (25 mm) of pavement depth can hold 0.5 inches (12.5 mm) of rain in theoretical. In this study, the depression storage rate of CDP was investigated under three different rainfall intensity scenarios which are 77 mm/hr (low), 153 mm/hr (medium), and 230 mm/hr (heavy) respectively whereby it function to monitoring the analytical trend line. The experiment was conducted in model box in the laboratory under fully saturated condition. It found that the CDP can performed to detent the water until 180 min of excess rainfall for all 2 year ARI, 5 year ARI, 10 year ARI, 20 year ARI, 50 year ARI and 100 year ARI with different rates. CDP's able to reduce the runoff up to 77% of the total rainfall volume. The result was proved the hollow cylindrical at centre of CDP very effective in runoff volume reduction according to the different ARI trend line projection.

Keywords: Depression Storage, Runoff Reduction, Cylindrical Detention Pond, Permeable Pavement, Storm Water Management, Fully Saturated.

1. INTRODUCTION

In recent years, rapid urbanization changes the land use by removes vegetation, green cover and replaces pervious area with increases in impervious surface with proximity to premix roads and concrete [1]. Since 1970's, the total population were urban dwellers increases to 30 percent and even more surprisingly in a year 1991, the urbanization had increase the population up to 50 percent and even keep on increasingly from year to year until now. Urban developments will also increase to meet the need of these increasing urban populations. Therefore, the impact of development has become one of the major causes that lead to flooding and the natural hydrologic cycle is disturbed where infiltration rate and ground water recharges

decreases, changes imposing high peak flows pattern of surface and river runoff volume increases [1–3].

Moreover, not surprisingly rate of flash flood in urban area in Malaysia in generally is expansion severe from year to year. Many urban cities have also increased the speed of overland flow and the amount of runoff because gray infrastructure has been designed to move water off streets as quickly as possible through gutters, storm drains, sewer pipes and other engineered collection systems and is discharged into nearby water bodies. Previously in Sarawak, a conventional drainage system has been designed to provide the fastest possible transport of storm water runoff out of the catchment into the receiving water as an effective mitigation flash flood [4]. Unfortunately, due to rapid development and high rainfall intensities, conventional drainage system, has led to high potential occurrence of flash flood at the downstream of the catchments.

*Author to whom correspondence should be addressed.