



Faculty of Engineering

**SOIL EROSION AND SEDIMENT YIELD AT CONSTRUCTION  
SITE - A CASE STUDY**

**LAW DAH LIT**

**Master Engineering by Coursework**

**(Civil Engineering)**

**2012**

Soil Erosion and Sediment Yield at Construction Site - A Case Study

LAW DAH LIT

This project is submitted in partial fulfillment of the requirements for  
Master of Engineering (Civil)

Faculty of Engineering

UNIVERSITI MALAYSIA SARAWAK

2012

*Humbly dedicated especially to my family members for continuous support, love and care:*

***My beloved Father and Mother,***

*Law Puong Chui*

*Wong Kiu Chuo*

***My siblings,***

*Law Chai Lit*

*Law Lit Ling*

***My Wife,***

*Ling Siew Ching*

***To my Supervisor and Co-supervisor***

*Prof Dr Ir Law Puong Ling*

*Dr Siti Noor linda Taib*

***Also to ALL My Friends,***

*Thanks for Love and Encouragement*

# ACKNOWLEDGEMENTS

First and foremost, I would like to express my sincere gratitude to my supervisor Prof Dr Ir Law Puong Ling who had guided me along the entire course of the research project and provided useful theoretical guidance and suggestion during my thesis writing. He has always been enthusiastic in checking my work for accuracy, assisting me with problems and offering numerous suggestions for improvement. I am also very thankful to my Co-supervisor, Dr Siti Norlinda Taib who has been very supportive in giving valuable guidance and patience that enabled me to make this research project a success.

Besides, I gratefully acknowledge all the technicians of civil and environmental laboratories, and my friends and seniors for their technical help during the experimental stage. My sincere appreciation also extends to Drainage and Irrigation Department (DID) for the cooperation and willingness in sharing knowledge and giving useful information and reference books.

This is the best moment to thank you for all the help, support, and perhaps success always with us. Finally, my deepest gratitude goes to my family members for their love, patience and support throughout the entire duration of my study that led to the successful completion of this thesis. Thank you all for your loving and understanding.

# ABSTRACT

Malaysia is currently undergoing rapid development towards urbanization and there has been an increasing concern over soil erosion and sedimentation issues. This is because the dynamic nature of soil erosion and sedimentation process depend on several factors, which include locality, climate, management, land use and cover, and also the extent of exposure of bare soil during construction activities. In order to estimate on-site and off-site impacts by soil erosion and transport of pollutant out of site, the mapping and computing methods with various variables would produce information that can be applied in the construction activities. In this research, soil erosion and sediment assessments were carried out for cut-and-fill activities at Samalaju Industrial Park, Bintulu, Sarawak. In this research, two equations called Revised Universal Soil Loss Equation (RUSLE) and Modified Universal Soil Loss Equation (MUSLE) equations were used to provide an assessment on soil erosion and sediment yield during pre-construction, during construction and post-construction periods.

Based on the results obtained, RUSLE values (soil erosion rates) show that soil erosion rates can be categorized as moderately high, especially during construction and operation phases. On the other hand, MUSLE values (sediment yield per storm event) also show that the highest sediment yield occurred during construction and operation phases. However, the amount of deposited sediment would vary from year to year. This situation could be due to the changes in rainfall patterns. The computed sedimentation data would provide a clear picture and understanding on the amount of sediment

deposited on site. To minimize potential erosion and sedimentation rates, there is a need to implement Best Management Practices (BMPs) for maximum protection of environment. In this research, it can be concluded that useful tools and methods for management of construction activities are the prime considerations to minimize soil erosion rate and sediment yield. Besides, there is a need to carry out regular inspection and maintenance on mitigation or control measures.

# ABSTRAK

Pada masa kini, Malaysia di bawah pembangunan yang pesat dan isu-isu hakisan tanah dan pendedahan semakin menjadi sehingga menimbulkan kebimbangan. Ini disebabkan terdapat beberapa factor yang menyumbangkan sifat dinamik hakisan tanah dan proses pendedahan iaitu iklim setempat, faktor pengurusan, penggunaan tanah dan perlindungan dan juga termasuk pendedahan tanah semasa aktiviti pembinaan. Untuk memperolehi penilaian data di dalam tapak dan juga kesan di luar tapak oleh hakisan tanah dan pengaliran bahan pencemar keluar dari tapak, kaedah pemetaan dan pengkomputeran dengan pelbagai pembolehubah boleh menghasilkan maklumat semasa aktiviti pembinaan. Penilaian hakisan tanah dan pendedahan telah dijalankan untuk aktiviti-aktiviti pembinaan tapak potong dan mengisi di Taman Perindustrian Samalaju, Bintulu Sarawak. Dalam projek ini, dua persamaan yang ringkas iaitu persamaan RUSLE dan MUSLE telah digunakan dengan memberi ideal yang jelas dan juga boleh digunakan sepanjang tempoh pembinaan untuk menilai potensi kadar hakisan tertentu dan juga kesan pendedahan bagi tapak projek.

Berdasarkan keputusan, nilai RUSLE menunjukkan bahawa kadar hakisan tanah boleh dikategori dalam sederhana tinggi terutama semasa dalam fasa pembinaan dan fasa operasi. Di samping itu, nilai MUSLE juga menunjukkan bahawa pendedahan yang tertinggi berlaku semasa dalam fasa pembinaan dan fasa operasi. Walau bagaimanapun, terdapat pengubahan untuk pendedahan dari setahun ke setahun. Keadaan ini disebabkan oleh perubahan pelbagai corak hujan dari tahun ke tahun. Dengan adanya anggaran kasar bagi pendedahan boleh memberi gambaran yang jelas dan memahami

jumlah pemendapan yang yang didepositkan keluar dari tapak. Dengan adanya jankaan pemendapan data langkah-langkah kawalan boleh disediakan boleh mengurangkan potensi hakisan tanah dan pemendapan dalam usaha untuk memaksimumkan perlindungan alam sekitar.

Sementara itu, langkah-langkah kawalan yang sesuai mesti disediakan untuk mengurangkan potensi hakisan tanah dan pemendapan melalui analisis data dengan perbandingan di antara kawasan kawalan dan kawasan tidak kawalan. Oleh itu, kaedah kaedah dan penggunaan peralatan yang berkean merupakan pertimbangan yang utama untuk pengurusan aktiviti pembinaan untuk mengurangkan kadar hakisan tanah dan hasil pemendapan dan meningkatkan perlindungan alam sekitar. Selain itu, untuk mendapatkan penilaian hasil yang berkesan, pemeriksaan dan penyelenggaraan yang kerap mestilah dilaksanakan.

# TABLE OF CONTENTS

	Pages
Acknowledgments	ii
Abstract	iii
Abstrak	v
Table of Contents	vii
List of Tables	xii
List of Figures	xv
List of Abbreviations	xviii
CHAPTER 1 INTRODUCTION	
1.1 Background of Study	1
1.2 Problem Statement	3
1.3 Research Aims	6
1.4 Hypothesis	7
1.5 Scope of Work	7
1.5.1 Identification of a Project Site / Existing Site Conditions	7
1.5.2 Topography	11
1.5.3 Geology and Soil	11
1.5.4 Climate	12
1.5.5 Catchment System	12
1.6 Project Outline	13

## CHAPTER 2 LITERATURE REVIEW

2.1	Introduction	15
2.2	Soil Erosion and Sediment Yield of Construction Development	17
2.2.1	Types of Soil Erosion	21
2.3	Soil Erosion and Sediment Yield	24
2.3.1	Revised Universal Soil-Loss Equation (RUSLE)	24
2.3.1.1	Climate	26
2.3.1.2	Soil Erodibility	28
2.3.1.3	Site Topography	32
2.3.1.4	Vegetative Cover	36
2.3.1.5	Support Practice	37
2.3.2	Modified Universal Soil-Loss Equation (MUSLE)	38
2.3.2.1	Rational Formulae	39
2.3.2.2	Hydrographs	40
2.3.2.3	SCS Curve Number Runoffs	42
2.4	Erosion and Sediment Control Plan (ESCP)	44
2.5	Best Management Practices (BMPs)	46
2.5.1	Runoff management / Runoff Control	51
2.5.1.1	Factors Affecting Runoff	52
2.5.1.2	Runoff Control BMPs	57
2.5.2	Soil Erosion Control	58
2.5.2.1	Erosion Control BMPs	59

	2.5.3	Sediment Yield Control	63
		2.5.3.1 Sediment Control BMPs	66
	2.5.4	Inspection and Maintenance	68
	2.6	Conclusions	69
CHAPTER 3	METHODOLOGY		
	3.1	Introduction	70
	3.2	Site Investigation and Assessment	72
		3.2.1 Identification of Study Area	72
		3.2.2 Compute the Soil Erosion and Sediment Yield Potential	73
		3.2.2.1 RUSLE	73
		3.2.2.2 MUSLE	84
	3.3	Proposed Erosion and Sediment Control Plan (ESCP) Based on Best Management Practices (BMPs)	91
		3.3.1 Runoff Management BMPs	92
		3.3.2 Soil Erosion / Stabilization Control	93
		3.3.3 Sediment Control	93
		3.3.4 Inspection and Maintenance	97
	3.4	Conclusions	98
CHAPTER 4	RESULTS AND DISCUSSION		
	4.1	Introduction	99
	4.2	Determination of Site Factor of Potential Soil Erosion Rate and Sediment Yield during Different	100

	Construction Periods	
4.2.1	Rainfall-Runoff Erosivity, R	100
4.2.2	Soil Erodibility, K	100
4.2.3	Slope Length and Steepness, LS	102
4.2.4	Estimating Cover Management Factor, C	104
4.2.5	Estimating Erosion Control Practice Factor, P	105
4.2.6	Estimating Peak Discharge, $Q_p$	106
4.2.7	Computing the Volume of Runoff, V	112
4.3	Soil Erosion Rate and Sediment Yield for Different Construction Phases	114
4.3.1	Summary	117
4.4	Purposed Erosion and Sediment Control Plan	117
4.4.1	Design Objectives	118
4.4.2	Temporary Erosion and Sediment Control Measures	118
4.4.2.1	Soil Erosion Control	118
4.4.2.2	Runoff Control	122
4.4.2.3	Sediment Control	123
4.4.3	Permanent Erosion and Sediment Control	127
4.4.3.1	Erosion Control	127
4.4.3.2	Runoff and Sediment Control	127
4.5	Predicted Soil Erosion Rates and Sediment Yields after Implementation of Control Measures during Different Construction Phases	128
4.5.1	Summary	131

4.6	Comprehensive Erosion and Sediment Control Plan	131
4.6.1	Inspection and Maintenance	137
4.6.1.1	Water Quality Monitoring	137
4.6.1.2	Permanent Stabilization	137
4.6.1.3	Structural Control BMPs	138
4.7	Conclusions	139
CHAPTER 5	CONCLUSIONS AND RECOMMENDATIONS	140
	BIBLIOGRAPHY AND REFERENCES	143
APPENDICES		
Appendix A:	METEOROLOGICAL DATA	
Appendix B:	SOIL CLASSIFICATION	
Appendix C:	SOIL TEST REPORTS	
Appendix D:	SOIL PERMEABILITY TESTS	
Appendix E:	EFFECTIVENESS FACTORS OF SOIL EROSION PREVENT AND SEDIMENT CONTROL	
Appendix F:	NATIONAL WATER QUALITY STANDARD FOR MALAYSIA (NWQSM)	

# LIST OF TABLES

		Pages
Table 2.1	Classification of Construction	18
Table 2.2	Potential Significant Environmental Impact during Construction	19
Table 2.3	Receiving Environment and Sedimentation Issues	20
Table 2.4	Types of Erosion	21
Table 2.5	Classification of Potential Soil Loss	26
Table 2.6	Classification of Rainfall Intensity	27
Table 2.7	Erodibility of Five Common Malaysia Soil Series	30
Table 2.8	Soil Loss from Various Segments Caused by Runoff	33
Table 2.9	LS Factor for Construction Sites	35
Table 2.10	BMP Implementation and Sequencing	49
Table 2.11	BMPs Criteria and Requirements for Application	50
Table 2.12	Methods and Functions BMPs	58

Table 3.1	USDA Soil Structural Classes	79
Table 3.2	USDA Soil Permeability Classes	79
Table 3.3	LS Factor for Construction Sites	83
Table 3.4	Cover Management Factor (C) – Construction Sites	85
Table 3.5	Surface Condition for Construction Sites	86
Table 3.6	Runoff Coefficient for Rational Equation	88
Table 3.7	Hydrology Soil Groups	90
Table 3.8	Runoff Curve Numbers for Undeveloped Land	91
Table 4.1	Rainfall-Runoff Erosivity, R Factor for Year 2011	100
Table 4.2	Particle Size Analyses Results for Samples Collected from 12 Borehole data	101
Table 4.3	Calculated Soil Erodibility, K Factor of Study Area	102
Table 4.4	LS Factor of Each Slope Class during Pre-Construction Phases	102
Table 4.5	LS Factor of Each Slope Class for Construction & Operation Phases	103

Table 4.6	C Factor for Different Construction Phases at Project Site	104
Table 4.7	P Factor for Different Construction Phases	105
Table 4.8	Runoff Coefficient for Different Construction Phases	106
Table 4.9	Peak Flow, $Q_p$ for Different Construction Phases	111
Table 4.10	Runoff Curve Number for Different Construction Phases	113
Table 4.11	Runoff Volume, $V$ for Different Construction Phases	113
Table 4.12	Predicted Soil Erosion Rates under Various Conditions during Different Construction Phases	116
Table 4.13	Predicted Sediment Yields under Various Conditions during Different Construction Phases	116
Table 4.14	Soil Erosion Rates after Implementation of BMPs	129
Table 4.15	Sediment Yield after Implementation of BMPs	130

# LIST OF FIGURES

	Pages	
Figure 1.1	Locality Plan of Bintulu-Similajau Area	8
Figure 1.2	Boundary Area of the Entire Proposed Project Site	9
Figure 1.3	Site Plan of the Proposed Project	10
Figure 2.1	Classification of Soil Texture	30
Figure 2.2	Eroding and Depositional Portions	33
Figure 2.3	Simple Storm Hydrographs	41
Figure 2.4	Component of Unit Hydrograph	41
Figure 2.5	Hydrological Cycle	51
Figure 3.1	Process Flow of Thesis	73
Figure 3.2	Soil Erodibility Nomograph	78
Figure 3.3	USDA Grain Sizes (mm) for Differentiating Soil Fractions	79
Figure 3.4	Slope Length on Existing Countour during Pre-Construction Phase	81

Figure 3.5	Slope Length on Proposed Elevation during Construction Phase	82
Figure 3.6	Typical steps for Soil Erosion and Sediment Control Planning	93
Figure 3.7	Runoff Management	96
Figure 3.8	Soil Erosion Control	97
Figure 3.9	Sediment Control	98
Figure 4.1	Catchment System on Existing Topography during Pre-Construction Phase	107
Figure 4.2	Pattern of Temporary Drainage Flow during Construction Phase	108
Figure 4.3	Catchment Area on Existing Topography during Pre-Construction Phase	109
Figure 4.4	Catchment Area during Construction Phase	110
Figure 4.5	Proposed Method of Filling on Site	119
Figure 4.6	Proposed Drain Pipe System	120
Figure 4.7	Proposed Temporary Seeding on Slope	121
Figure 4.8	Proposed Turfing Pattern on Slope	123
Figure 4.9	Proposed Check Dams on Temporary Drainage	126

Figure 4.10	Proposed Silt Fence Specification and Installation	124
Figure 4.11	Proposed Silt Traps and Specifications	125
Figure 4.12	Proposed Stabilized Construction Exits and Specification	126
Figure 4.13	Temporary Erosion Control Measures – Proposed Earth Filling Method	132
Figure 4.14	Temporary Erosion Control Measure – Propose Filling Area With Divided Phases and Seeding	133
Figure 4.15	Temporary Sediment and Runoff Control Measures – Proposed Earth drain, Silt Trap and Check Dams	134
Figure 4.16	Temporary Sediment Control Measure – Propose Stabilized Construction Exits and Silt Fence Along Site Perimeter	135
Figure 4.17	Permanent Runoff, Erosion and Sediment Control Measures – Proposed Seeding, Drainage, and Silt Trap System	136

# LIST OF ABBREVIATIONS

BMPs	-	Best Management Practices
C	-	Cover-Management Factor
CN	-	Curve Number
CPESC	-	Certified Professional in Erosion and Sediment Control
DID	-	Department of Irrigation and Drainage
ESC	-	Erosion and Sediment Control
ESCP	-	Erosion and Sediment Control Plan
ha	-	Hectare
HSGs	-	Hydrologic Soil Groups
I	-	Intensity of Rainfall
$I_a$	-	Initial Abstraction
IDF	-	Rainfall Intensity, Duration and Frequency Curve
j	-	Joule
K	-	Soil Erodibility
LS	-	Slope Length and Steepness Factor
MUSLE	-	Modified Universal Soil-Loss Equation

N-P-K	-	Nitrogen-Phosphorus-Potassium
NWQSM	-	National Water Quality Standard of Malaysia
OM	-	Organic Matter Content
p	-	Erosion Control Practice Factor
Q <sub>p</sub>	-	Peak Flow
R	-	Rainfall/Runoff Erosivity
RUSLE	-	Revised Universal Soil-Loss Equation
SSTS	-	Soil Stabilization for Temporary Slopes
t	-	Tonnes
t <sub>c</sub>	-	Time of Concentration
t <sub>o</sub>	-	Time of Overland Flow
TRMs	-	Turf Reinforcement Mats
t <sub>t</sub>	-	Time of Travel
USDA	-	United States Department of Agriculture
USLE	-	Universal Soil-Loss Equation
V	-	Volume of Runoff
WEPP	-	Water Erosion Prediction Project
yr	-	Year

# CHAPTER 1

## INTRODUCTION

### 1.1 Background of study

Soil is subjected to natural weathering and erosion. Natural, geologic, erosion by water, wind and ice has been occurring at relatively slow rate since the earth was formed. But the construction activities and large earth-moving projects enhance the erosion dramatically, mainly by exposing large areas of soil to rain and running water. If this runoff is not treated properly, it will cause serious siltation of nearby watercourses. In many developed countries including Malaysia, soil is highly susceptible to erosion due to the demand of development. Therefore, construction site erosion and sediment controls are the main challenging problems for engineers in real-world environmental management issues (Theakston, 1988).

In Malaysia, there has been an increasing concern over soil erosion consequences of deforestation related to land conversion for highway, logging activities, industrial or urbanization purposes (Brooks, Richard & Spencer, 1993). Therefore, construction engineers and landscape architects have a number of 'tools'

at their disposal to keep soil onsite. These erosion and sediment control practitioners are required to identify the most appropriate and cost-effective best management practices (BMPs) for their erosion control plan.

In nature, there are two major types of erosion, i.e. by water and wind. For Malaysian environment, water is the most significant erosion due to high mean of annual rainfall, storm frequency and density (Department of Irrigation and Drainage, 2001). Besides, according to (Schueler & Lugbill, 1990) in construction development, it has been found that sediments from construction sites typically consist of larger percentage of smaller particles such as silt and clay than the parent soil. This is because of the small size of the unconsolidated particles from construction in storm water runoff that are displaced easily than the larger particles in compacted soil.

Therefore, there are six principles to be considered in preparation of a Erosion and Sediment Control Plan (ESCP) which include planning considerations, vegetative stabilization, physical stabilization, diversion of runoff, flow velocity reduction, and sediment Trapping/Filtering need to be implemented for erosion and sediment control (ESC) activities during construction development (Md Noh, 2006). The utilization of ESCP for construction development areas becomes compulsory since October 2005 after being endorsement by the National Council for Local Government. For every development projects with greater 1 hectare has to submit ESCP and Earthwork Plan to DID for review and endorsement prior to granting of approval by Local Authority. For area that is less than 1 ha, ESC measures shall be embedded in the Earthwork Plan allowing small scale development to waive full ESCP submission.

## **1.2 Problem Statement**

Recently urban development was particularly rapid in Malaysia. There are further hillside development has been rapid in the last two decades in Malaysia and has causing in acute environmental problem in many locations (Department of Environment, 2008). Apart from urban expansion, development has also occurred in inland hilly areas as well as near coastlines and on islands for industrial purposes like at Bintulu region Samalaju Industrial Parks. Planning and achieving sustainable development in such environment is particularly important in regard to erosion and sedimentation, slope stability management, drainage, and flash flood (Department of Irrigation and Drainage, 2001). An adverse environmental effect of urban growth in Malaysia has been frequent occurrence of excessive soil losses from sites cleared of vegetation but awaiting development and from construction sites. There has also been deterioration in a number of water courses (Department of Environment, 1995).

There are two major type of erosion, by wind and by water. Under Malaysian conditions, erosion by water is the most significant due to high mean annual rainfall, storm density and frequency. Higher rates of erosion will occur when the vegetation cover is disturbed or removed. Once the vegetation is cleared, interception of rainfall will be greatly reduced. This will result in a drastic increase in surface runoff velocity and volume. Increase runoff (especially on hilly terrains) will certainly cause substantial soil erosion. Erosion by running water may take place in the form of rill or gully erosion, notably in loose sandy granitic soils or reworked residual soils (University of Malaya Consultancy Unit, 2003).